

Road Rules 2007

10-22-07

New Language

~~Proposed Deletions~~

**Amend 14 CCR 895.1. Definitions**

Abandoned Road means a logging road on which proactive measures have been applied to effectively remove it from the permanent road network.

~~Abandonment~~ means leaving a logging road reasonably impassable to standard production four wheel drive highway vehicles, and leaving a logging road and landings, in a condition which provides for long term functioning of erosion controls with little or no continuing maintenance.

Abandonment means taking proactive measures to effectively remove an existing logging road, landing, or logging road watercourse crossing from the permanent road network.

**Act** means...

~~Active Erosion Site~~ means an area where erosion and sediment production are ongoing during any period of the year.

**Comment [p1]:** Deleted; ASP rules delete term and incorporates clarification in revised 916.9(o).

1 **Active Nest** means...

2

3

4 **Beneficial Use** means...

5

6 ~~**Berm** means a curb or dike constructed to control water and prevent~~  
7 ~~roadway runoff waters from discharging onto roadside slopes and/or to~~  
8 ~~provide material for subsequent road maintenance.~~

9 **Berm** means a curb, dike, or linear mound of earth that is constructed  
10 to control water and direct roadway runoff waters or that has  
11 developed through road grading activities.

12

13 **Board** see PRC 4521.3.

14

15

16 **Confidential Archaeological Letter** means...

17

18 **Connected Headwall Swale** means a geomorphic feature consisting of a  
19 bowl-shaped, concave depression with convergent slopes, typically of  
20 65 percent or greater steepness, that is connected to a watercourse or  
21 lake by way of a continuous linear depression and that has been  
22 sculpted over geologic time by shallow landslide events. The slope  
23 profile is typically smooth and unbroken by benches, but **may** be  
24 interrupted by recent landslide deposits or scars. Emergent  
25 groundwater and wet areas **may** exist at the base of the swale. Soil

Formatted: Highlight

Formatted: Highlight

1 and colluvium depth is typically greatest at the axis of the swale,  
2 thinning to either side.

3

4 **Countable Tree** see 4528(b).

5

6 **Critical Dip** means a constructed dip across a logging road surface  
7 immediately down grade from, or over, a culverted logging road  
8 watercourse crossing that functions to prevent crossing overflow from  
9 draining down the road.

10

11 **Critical Period** means...

12

13 **Crop of Trees**...

14

15 **Crowning** means creating a road surface with a convex cross sectional  
16 profile that drains runoff toward both sides of the road.

17

18 **Cumulative Impacts** means...

19

20

21 **Danger Tree** means...

22

23 **Deactivated Road** means a logging road that is part of the permanent  
24 road network where proactive measures have been applied to prevent  
25 active use.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

**Deactivation** means taking the proactive measures necessary to prevent the active use of an existing logging road, landing, or logging road watercourse crossing.

**Decadent and Deformed Trees of Value to Wildlife** means...

**Emergency** means...

**End-Hauling** means the removal and transport of ~~excavated~~ excess material ~~to prevent sidecast.~~

**Energy Dissipator** means...

**Estimated Erosion Potential (For the Northern Forest District:)** means...

**Excess Material** means excavated material that is not used ~~or needed~~ as a functional part of the road or ~~a~~ landing. Excess material is synonymous with spoils.

**Executive Officer** means...

1 **Feasible** means...

2

3 ~~**Fifty-Year Flood Flow** means that magnitude of peak flow which one~~  
4 ~~would expect to be equaled or exceeded, on the average, once every 50~~  
5 ~~years. This flow shall be estimated by empirical relationships~~  
6 ~~between precipitation and watershed characteristics and runoff and~~  
7 ~~then may be modified by direct channel cross section measurements and~~  
8 ~~local experience with a two (2) percent chance of annual occurrence or~~  
9 ~~that would, on the average, occur once every 50 years. This flow~~  
10 ~~shall be estimated by flood flow measurement records and relationships~~  
11 ~~or by empirical relationships between precipitation, watershed~~  
12 ~~characteristics, and runoff, and **may** be modified by direct channel~~  
13 ~~cross section measurements and local **experience**.~~

Formatted: Highlight

Formatted: Highlight

Comment [p2]: Deleted from proposal; ASP definition of "flood flow" addresses.

14

15 **Fill** means material that is mechanically placed ~~in low areas~~ and built  
16 up in lifts to form a the roadbed or landing surface. Fill includes  
17 the material placed around culverts and related drainage structures at  
18 logging road watercourse crossings.

19

20 **Fire Protection Zone** (For the Coast and the Southern Forest District:)  
21 means...

22

23 **Fire Protection Zone** (For the Coast and the Southern Forest District:)  
24 means...

25

1 Ford means a logging road watercourse crossing where the road grade  
2 dips through the watercourse channel.

3  
4 **Fuelbreak** see PRC 4528(e).

5  
6  
7 **Hard Frozen Conditions** means...

8  
9 Harvest Area means the area where trees are felled and removed.

10  
11 **Harvesting Method** means...

12  
13 **Inner Gorge** means...

14  
15 Insloping means shaping the road surface to drain toward a cutbank.

16  
17 **Intermediate Treatments** means...

18  
19  
20 **Occupied Nest** means...

21  
22 ~~One Hundred Year Flood Flow means that magnitude of peak flow with a~~  
23 ~~one (1) percent chance of annual occurrence or that, **which**, on the~~  
24 ~~average, occur once every 100 years. This flow shall be estimated by~~  
25 ~~flood flow measurement records and relationships or by empirical~~  
~~relationships between precipitation, watershed characteristics, and~~

Formatted: Highlight

1 ~~runoff, and [REDACTED] be modified by direct channel cross section~~  
2 ~~measurements and local experience.~~

Formatted: Highlight

Comment [p3]: Deleted from proposal; ASF definition of "flood flow" addresses.

3  
4 Outsloping means shaping the road surface to drain toward the outside  
5 edge.

6  
7 **Overhanging Bank** means...

8  
9  
10 **Perch Tree** means...

11  
12 ~~**Permanent Road** means a road which is planned and constructed to be~~  
13 ~~part of a permanent all-season transportation facility. These roads~~  
14 ~~have a surface which is suitable for the hauling of forest products~~  
15 ~~throughout the entire winter period and have drainage structures, if~~  
16 ~~any, at watercourse crossings which will accommodate the fifty year~~  
17 ~~flood flow. Normally they are maintained during the winter period. a~~  
18 logging road that is part of the permanent road network and is  
19 planned, constructed, and maintained for year-round use.

20  
21 **Permanent Road Network** means the permanent, seasonal, ~~and temporary,~~  
22 and deactivated roads that provide the infrastructure necessary for  
23 timber operations and forest management.

1 **Permanent Watercourse Crossing** means a watercourse crossing that ~~will~~  
2 ~~be constructed to accommodate the estimated fifty year flood flow and~~  
3 will remain in place when timber operations have been completed.

4  
5 **Person** see PRC 4525.

6  
7  
8 **Predominant Trees** are...

9  
10 **Prescribed Maintenance Period** means the time period, beginning with  
11 filing of the work completion report, provided that the report is  
12 subsequently approved, during which erosion controls ~~which~~ that are  
13 required and constructed as part of ~~a~~ timber operations must be  
14 maintained in a functional condition. ~~The period shall not exceed~~  
15 ~~three years from the filing of the work completion report provided~~  
16 ~~that the report is subsequently approved by the director.~~

17  
18 **Professional Archaeologist** means...

19  
20  
21 **Public fire** agency...

22  
23 **Public Road** means a road open to the general public which is: (a) in  
24 ~~the~~ a Federal, State, ~~or~~ County, or City road system, or (b) a road on  
25 which a public agency has deeded, unlimited easement.

1 **Quality of Water** means...

2

3

4 **Road Failure** means...

5

6 **Road Maintenance** means activities involving manipulation of the  
7 logging road prism to maintain stable operating surfaces, functioning  
8 logging road drainage facilities and structures, and stable cutbanks  
9 and fill slopes.

10

11 **Rolling dip** means...

12

13

14 **Screening Trees** means...

15

16 **Seasonal Road** means a ~~road which is planned and constructed as part of~~  
17 ~~a permanent transportation facility where: 1) commercial hauling may~~  
18 ~~be discontinued during the winter period, or 2) the landowner desires~~  
19 ~~continuation of access for fire control, forest management activities,~~  
20 ~~Christmas tree growing, or for occasional or incidental use for~~  
21 ~~harvesting of minor forest products, or similar activities. These~~  
22 ~~roads have a surface adequate for hauling of forest products in the~~  
23 ~~non-winter periods, and in the extended dry periods or hard frozen~~  
24 ~~conditions occurring during the winter period, and have drainage~~  
25 ~~structures, if any, at watercourse crossing which will accommodate the~~  
~~fifty year flood flow. Some maintenance usually is required logging~~

1 road that is part of the permanent road network where use is generally  
2 discontinued during the winter period.

3  
4 **Seed Tree** a...

5  
6 **Sensitive Species** means...

7  
8 **Sidecast** means excess earthen material pushed or dumped ~~to or~~ over the  
9 side of a road or landings.

10  
11 **Significant Adverse Impact on the Environment** means...

12  
13  
14 **Spotted Owl Resource Plan** means...

15  
16 ~~**Option 1: Stable operating surface** means a road or landing surface~~  
17 ~~that can support vehicular traffic and that routes water off of the~~  
18 ~~road surface during any period of intended use without: (1)~~  
19 ~~development of tire ruts that concentrate runoff on the road surface~~  
20 ~~for more than 50 feet and (2) pumping of fine grained material onto~~  
21 ~~the road surface that **may** require mechanical removal to continue~~  
22 ~~using the road. A stable operating surface shall include a~~  
23 ~~structurally sound road base appropriate for the intended use.~~

24 ~~**Option 2: Stable operating surface** means a road or landing surface~~  
25 ~~that can support vehicular traffic and that routes water off of the~~  
~~road surface or into drainage facilities without concentrating flow in~~

Formatted: Highlight

~~ruts (tire tracks), pumping of the road bed, or ponding flow in depressions, which would lead to the transport of fine grained materials from the road or landing surface into watercourses or lakes in quantities deleterious to the beneficial uses of water. A stable operating surface shall include a structurally sound road base appropriate for the intended use.~~

Formatted: Highlight

Formatted: Highlight

**Comment [p4]:** The BOF adopted a new definition under the ASP 2009 rules that apply statewide and which does not include linkage between road condition and associated WQ impacts. The adopted definition relies on the inclusion of specific rule subsection language regarding the prevention of deleterious water quality impacts.

**Stand vigor** means...

**Stream** see PRC 4528(f).

~~**Stressing Storm** means a storm that yields at least a 10-year flood flow.~~

**Comment [p5]:** NOTE: concept was rejected as a categorical exception under the ASP rules and therefore has been deleted.

**Substantial adverse change** means...

**Take** means...

**Temporary Road** means a logging road that is to be used only during the timber operations and that will be deactivated or abandoned upon completion of use. ~~These roads have a surface adequate for seasonal logging use and have drainage structures, if any, adequate to carry the anticipated flow of water during the period of use.~~

1 ~~Ten-Year Flood Flow means that magnitude of peak flow with a ten (10)~~  
2 ~~percent chance of annual occurrence that **occurs**, on the average, occur~~  
3 ~~once every 10 years. This flow shall be estimated by flood flow~~  
4 ~~measurement records and relationships or by empirical relationships~~  
5 ~~between precipitation, watershed characteristics, and runoff, and **may**~~  
6 ~~be modified by direct channel cross section measurements and local~~  
7 ~~experience.~~

Formatted: Highlight

Formatted: Highlight

Comment [p6]: NOTE: concept was rejected as a categorical exception under the ASP rules and therefore has been deleted.

8  
9 **THP** means...

10  
11 **Through Cut** means a section of road that lies below the adjacent  
12 ground level on both sides of the road.

13  
14 **Through Fill** means a section of road upon constructed fill that lies  
15 above the adjacent ground level on both sides of the road.

16  
17 **Tight-Lining** means...

18

19

20

21

22

23

24

25

1 **Amend 914.8, 934.8, 954.8 Tractor Road Watercourse Crossing**

2  
3 (d) ~~Tractor road~~ ~~W~~watercourse crossing facilities ~~not constructed to~~  
4 ~~permanent crossing standards on tractor roads~~ shall be removed and  
5 stabilized before the beginning of the winter period. ~~If a~~  
6 ~~watercourse crossing is to be removed, it shall be removed in~~  
7 ~~accordance with~~ to the standards of 14 CCR § 923.3(d) [943.3(d),  
8 ~~963.3(d)] 923.17(a)-(c) [943.17(a)-(c), 963.17(a)-(c)].~~ The RPF 25  
9 propose an exception if explained and justified in the plan and found  
10 by the Director to be in conformance with this article.

Formatted: Highlight

11  
12 **Amend 916.3, 936.3, 956.3. General Limitations Near Watercourses,**  
13 **Lakes, Marshes, Meadows and Other Wet Areas**

14  
15 (c) The timber operator shall not ~~construct or reconstruct roads,~~  
16 ~~construct or use tractor roads or landings~~ in Class I, II, III or IV  
17 watercourses, in the WLPZ, marshes, wet meadows, and other wet areas  
18 unless when explained and justified in the ~~THP~~ plan by the RPF, and  
19 approved by the Director, except as follows:

20 (1) At prepared tractor road crossings as described in 14 CCR §  
21 914.8(b) [934.8(b), 954.8(b)].

22 (2) Crossings of Class III watercourses ~~which~~ that are dry at  
23 the time of ~~timber operations~~ use.

24 ~~(3) At existing road crossings.~~

25 ~~(4)~~ (3) At new tractor ~~and~~ road crossings approved as part of  
the Fish and Game Code process (F&GC 1600 et seq.).

1 Use of existing roads is addressed in 916.4(a) [936.4(a),  
2 956.4(a)].

3  
4 **Amend 916.9, 936.9, 956.9. Protection and Restoration of the**  
5 **Beneficial Functions of the Riparian Zone in Watersheds with**  
6 **Listed ~~Threatened or Impaired Values~~ Anadromous Salmonids.**

8 (a) - ~~(ge)~~ [No change]

**Comment [p7]:** Change to reflect ASP rules

9 **(f) Class I watercourses -**

**Comment [p8]:** New ASP rule 916.9(f) incorporated.

10 (1) For Class I watercourses, where fish are always or seasonally  
11 present or where fish habitat is restorable, any plan involving timber  
12 operations within the WLPZ shall contain the following information:

13 (A) Clear and enforceable specifications of timber  
14 operations within the Class I WLPZ, including a description of how any  
15 disturbance, or log or tree cutting and removal shall be carried out  
16 to conform with 14 CCR §§ 916.2 [936.2, 956.2], subsection (a) and  
17 916.9 [936.9, 956.9], subsection (a).

18 ~~(B) A description of all existing permanent logging road~~  
19 ~~watercourse crossings.~~

**Comment [p9]:** Subsections (f) (1) (B) and (C) related to logging road watercourse crossings are moved to 923.11 (j) (1) and (3) [943, 963] et seq. NOTE: requirement (B) also specified in 1034 (jj) (3).

20 ~~(C) Clear and enforceable specifications describing how~~  
21 ~~these crossings are to be modified, used, and treated to minimize~~  
22 ~~risks, giving special attention to allowing fish to pass both upstream~~  
23 ~~and downstream during all life stages.~~

24 ~~(D) Clear and enforceable specifications for construction~~  
25 ~~and operation of any~~  
~~new crossing(s) of a Class I watercourse to prevent direct harm,~~

~~habitat degradation, water velocity increase, hindrance of fish passage, or other potential impairment of beneficial uses of water.~~

**Comment [p10]:** Moves to 923.12(m) (1).

(EB) Documentation of how proposed harvesting in the WLPZ contributes to the objectives of each zone stated in 14 CCR § 916.9 [936.9,956.9], subsection (c) and other goals in 14 CCR § 916.9 [936.9,956.9], subsection (a) (1)-(8). Documentation shall include the examinations, analysis, and other requirements listed in 14 CCR § 916.4 [936.4, 956.4], subsection (a).

(2) No Changes

(3) Class I watercourses with flood prone areas or channel migration zones: ...

(A-D) No Changes

(E) Preferred Management Practices in the Inner Zone A and B of Flood Prone Areas...

1., 2., and 3., No changes

~~4. Avoid Road and Landing Use: All new roads and landings shall be located outside of zone. When feasible, minimize use of existing roads and landings in the flood prone area. No servicing of equipment within the flood prone area. Exceptions include the use of roads and landings to accomplish actions to improved salmonid habitat conditions stated 14 CCR § 916.9 [936.9, 956.9]. subsection (f) (3) (E(1.) above.~~

**Comment [ts11]:** Requirements related to logging roads and landings and channel migration zones/flood prone areas have been moved to planning 923.1(g) and (h) and construction 923.4(r).

~~(5) (4) ...~~

~~(6) (5) ...~~

~~(7) (6) ...~~

1 ~~(8)~~ (7) ...

2 (F) Outer Zone No Changes.

3 ~~(h) For Class I waters, any plan involving timber operations within~~  
4 ~~the WLPZ shall contain the following information:~~

Comment [p12]: Old T/I rule  
916.9(h) deleted

5 ~~(1) A a clear and enforceable specification of how any~~  
6 ~~disturbance or log or tree cutting and removal within the Class I WLPZ~~  
7 ~~shall be carried out to conform with 14 CCR §§ 916.2 [936.2, 956.2] (a)~~  
8 ~~and 916.9 [936.9, 956.9] (a).~~

9 ~~(2) A description of all existing permanent crossings of Class~~  
10 ~~I waters by logging roads and clear specification regarding how these~~  
11 ~~crossings are to be modified, used, and treated to minimize risks,~~  
12 ~~giving special attention to allowing fish to pass both upstream and~~  
13 ~~downstream during all life stages.~~

14 ~~(3) Clear and enforceable specifications for construction and~~  
15 ~~operation of any new crossing of Class I waters to prevent direct~~  
16 ~~harm, habitat degradation, water velocity increase, hindrance of fish~~  
17 ~~passage, or other potential impairment of beneficial uses of water.~~

18 (ig) - (ji) [No change]

19 ~~(k) From October 15 to May 1, the following shall apply:~~

20 ~~(1) nNo timber operations shall take place unless the approved~~  
21 ~~plan incorporates a complete winter period operating plan pursuant to~~  
22 ~~14 CCR § 914.7(a) [934.7(a), 954.7(a)], .~~

23 ~~(2) uUnless the winter period operating plan proposes~~  
24 ~~operations during an extended period with low antecedent soil wetness,~~  
25 ~~no tractor roads shall be constructed, reconstructed, or used on~~  
~~slopes that are over 40 percent and within 200 feet of a Class I, II,~~

1 ~~or III watercourse, as measured from the watercourse or lake~~  
2 ~~transition line, and~~

3 ~~(3) Operation of trucks and heavy equipment on roads and~~  
4 ~~landings shall be limited to those with a stable operating surface.~~

5 **(k) Year-round logging road, landing and tractor road use limitations -**

6 From October 15 to May 1, the following shall apply: (1)no timber operations shall take place  
7 unless the approved plan incorporates a complete winter period operating plan pursuant to 14  
8 CCR § 914.7(a) [934.7(a), 954.7(a)], (2)unless the winter period operating plan proposes  
9 operations during an extended period with low antecedent soil wetness, no tractor roads shall  
10 be constructed, reconstructed, or used on slopes that are over 40 percent and within 200 feet of  
11 a Class I, II, or III watercourse, as measured from the watercourse or lake transition line, and  
12 operations of trucks and heavy on logging roads and landings shall be limited to those with a  
13 stable operating.

14 ~~(1) Logging roads, landings or Tr~~ tractor roads shall not be used when visibly turbid water  
15 from the road, landing or tractor road (skid trail) or an inside ditch associated with the logging  
16 road, landing or tractor road may reach a watercourse or lake in amounts sufficient to cause a  
17 turbidity increase in Class I, II, III or IV waters.

18 ~~(2) Log hauling on logging roads and landings shall be limited to those which are~~  
19 ~~hydrologically disconnected from watercourses to the extent feasible, and exhibit a~~  
20 ~~stable operating surface in conformance with (1) above.~~

21 ~~(3) Concurrent with use for log hauling, approaches to logging road watercourse~~  
22 ~~crossings shall be treated for erosion control as needed to minimize soil erosion and sediment~~  
23 ~~transport and to prevent the discharge of sediment into watercourses and lakes in quantities~~  
24 ~~deleterious to the beneficial uses of water.~~

**Comment [p13]:** . Subsection 916.9(k) is modified to only address year-round tractor road use limitations per the ASP rules; only revised (k)(1) is retained. The logging road, and landing limitations from the new (k)(1)-(4) are moved to 923.6(i)(1)(4).

~~(4) Concurrent with use for log hauling, all traveled surfaces of logging roads in a WLPZ or within any ELZ or EEZ designated for watercourse or lake protection shall be treated for erosion control as needed to minimize soil erosion and sediment transport and to prevent the discharge of sediment into watercourses and lakes in quantities deleterious to the beneficial uses of water.~~

~~(5) Grading to obtain a drier running surface more than one time before reincorporation of any resulting berms back into the road surface is prohibited.~~

**Comment [p14]:** Subsection 916.9 (k) (5) moves to 923.7(1) (1).

**(l) Extended Wet Weather Period** ~~Construction or reconstruction of logging roads, tractor roads, or landings shall not take place during the winter period unless the approved plan incorporates a complete winter period operating plan pursuant to 14 § CCR 914.7(a) [934.7(a), 954.7(a)] that specifically address such road construction. Use of logging roads, tractor roads, or landings shall not take place at any location where saturated soil conditions exist, where a stable logging road or landing operating surface does not exist, or when visibly turbid water from the road, landing, or skid trail surface or inside ditch may reach a watercourse or lake. Grading to obtain a drier running surface more than one time before reincorporation of any resulting berms back into the road surface is prohibited.~~ October 15 to May 1 shall be considered the extended wet weather period and the following shall apply:

**Comment [p15]:** Subsection 916.9(1) is modified to address only extended wet weather tractor operations conducted from October 15 to May 1 per the ASP rules; revised subsections (1)-(3) are retained. The logging road and landing limitations from the new (1)(1), (3) and (4) are moved to 923.6(i) (6)-(8).

**(1)** No timber operations shall take place unless the approved plan incorporates a complete winter period operating plan pursuant to 14 CCR § 914.7 [934.7, 954.7] subsection (a) that specifically addresses, where applicable, proposed ~~logging road, landing or~~ tractor road construction, reconstruction and use during the extended wet weather period. ~~Where logging road watercourse crossing construction or reconstruction is proposed an implementation schedule shall be specified.~~

1 (2) Unless the winter period operating plan proposes operations during an  
2 extended wet weather period with low antecedent soil wetness, no tractor roads shall be  
3 constructed, reconstructed, or used on slopes that are over 40 percent and within 200  
4 feet of a Class I, II, or III watercourse, as measured from the watercourse or lake  
5 transition line during the extended wet weather period, and

6 (3) ~~Logging roads, landings and T~~ tractor roads shall not be used when sediment from  
7 the ~~logging road, landing or~~ tractor road surface is transported to a watercourse or a drainage  
8 facility that discharges into a watercourse in amounts sufficient to cause a visible increase in  
9 turbidity in Class I, II, III, or IV waters.

10 (4) ~~Logging roads and landings shall not be used for log hauling when saturated soil~~  
11 ~~conditions result in the visible increase in turbidity specified in (3) above.~~

12  
13 ~~(1) Construction or reconstruction of logging roads, tractor roads,~~  
14 ~~or landings shall not take place during the winter period unless the~~  
15 ~~approved plan incorporates a complete winter period operating plan~~  
16 ~~pursuant to 14 § CCR 914.7(a) [934.7(a), 954.7(a)] that specifically~~  
17 ~~addresses such tractor road construction or reconstruction. Use of~~  
18 ~~logging roads, tractor roads, or landings shall not take place at any~~  
19 ~~location where saturated soil conditions exist, where a stable logging~~  
20 ~~road or landing operating surface does not exist, or when visibly~~  
21 ~~turbid water from the road, landing, or skid trail tractor road~~  
22 ~~surface or inside ditch may reach a watercourse or lake. Grading to~~  
23 ~~obtain a drier running surface more than one time before~~  
24 ~~reincorporation of any resulting berms back into the road surface is~~  
25 ~~prohibited.~~

Formatted: Highlight

(m) [No change]

1 \*\*\*\*\***(n) Treatments to stabilize soils** - Within the WLPZ, and within any ELZ or EEZ  
2 designated for watercourse or lake protection, treatments to stabilize soils, minimize soil  
3 erosion, and prevent the discharge of sediment into watercourses or lakes in amounts  
4 deleterious to aquatic species or the quality and beneficial uses of water, or that threaten to  
5 violate applicable water quality requirements, shall be described in the plan as follows. applied  
6 in accordance with the following standards:

7 ~~(1) The following requirements shall apply to all such treatments.~~

8 ~~(A) They shall be described in the plan.~~

9 ~~(B) For areas disturbed from May 1 through October 15, treatment shall be~~  
10 ~~completed prior to the start of any rain that causes overland flow across or along the disturbed~~  
11 ~~surface.~~

12 ~~(C) For areas disturbed from October 15 to May 1, treatment shall be~~  
13 ~~completed prior to any day for which a chance of rain of 30 percent or greater is forecast by the~~  
14 ~~National Weather Service or within 10 days, whichever is earlier.~~

15 ~~(3)(1) The treatment for other disturbed areas, including:~~ Soil stabilization is required for  
16 the following areas:

17 ~~(A) a~~Areas exceeding 100 contiguous square feet where timber operations have  
18 exposed bare soil.

19 ~~(B) a~~Approaches to tractor road watercourse crossings between the drainage  
20 facilities closest to the crossing.

21 ~~(C) Disturbed road cut banks and fills, and~~

22 ~~(D) a~~Any other area of disturbed soil that threatens to discharge sediment into  
23 waters in amounts deleterious to the quality and beneficial uses of water.

24 ~~(2) Soil stabilization treatment measures may include, but need not be limited to,~~  
25 removal, armoring with rip-rap, replanting, mulching, ~~rip-rapping,~~ grass seeding, installing  
commercial erosion control devices to manufacturer's specifications, or chemical soil stabilizers.

**Comment [p16]:** The ASP rule subsection of revised 916.9(n) is retained to address stabilization on tractor roads and other areas unrelated to logging road, landing and logging road watercourse crossings. Logging road and landing stabilization requirements from 916.9(n) are incorporated into subsections 923.5 (p) and for logging road watercourse crossings into 923.14 (b).

1 ~~Where straw, mulch, or slash is used, the minimum coverage shall be 90%, and any treated~~  
2 ~~area that has been subject to reuse or has less than 90% surface cover shall be treated again~~  
3  
4 ~~prior to the end of timber operations. The RPF may propose alternative treatments that will~~  
5 ~~achieve the same level of erosion control and sediment discharge prevention.~~

6 ~~(4) Where the undisturbed natural ground cover cannot effectively protect beneficial~~  
7 ~~uses of water from timber operations, the ground shall be treated by measures including, but not~~  
8 ~~limited to, seeding, mulching, or replanting, in order to retain and improve its natural ability to~~  
9 ~~filter sediment, minimize soil erosion, and stabilize banks of watercourses and lakes.~~

10  
11 (3) Where straw or slash mulch is used, the minimum straw coverage shall be 90  
12 percent, and any treated area that has been reused or has less than 90 percent surface cover  
13 shall be treated again by the end of timber operations.

14 (4) Where slash mulch is packed into the ground surface through the use of a tractor or  
15 equivalent piece of heavy equipment the minimum slash coverage shall be 75 percent.

16 (5) For areas disturbed from May 1 to October 15, treatment shall be completed prior to  
17 the start of any rain that causes overland flow across or along the disturbed surface that could  
18 deliver sediment into a watercourse or lake in quantities deleterious to the beneficial uses of  
19 water.

20 (6) For areas disturbed from October 15 to May 1, treatment shall be completed prior to  
21 any day for which a chance of rain of 30 percent or greater is forecast by the National Weather  
22 Service or within 10 days, whichever is earlier.

23 (7) Where the natural ability of ground cover is inadequate to protect beneficial uses of  
24 water by minimizing soil erosion or by filtering sediment, the plan shall specify protection  
25 measures to retain and improve the natural ability of the ground cover to filter sediment and  
minimize soil erosion.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

~~(a) Within the WLPZ, and within any ELZ or EEZ designated for watercourse or lake protection, treatments to stabilize soils, minimize soil erosion, and prevent the discharge of sediment into waters in amounts **excessive** to aquatic species or the quality and beneficial uses of water, or that threaten to violate applicable water quality requirements, shall be applied in accordance with the following standards:~~

~~(1) The following requirements shall apply to all such treatments.~~

~~(A) They shall be described in the plan.~~

~~(B) For areas disturbed from May 1 to October 15, treatment shall be completed prior to the start of any rain that causes overland flow across or along the disturbed surface.~~

~~(C) For areas disturbed from October 15 to May 1, treatment shall be completed prior to any day for which a chance of rain of 30 percent or greater is forecast by the National Weather Service or within 10 days, whichever is earlier.~~

~~(2) The traveled surface of logging roads shall be treated to prevent waterborne transport of sediment and concentration of runoff that results from timber operations.~~

~~(3) (2) The treatment for other disturbed areas, including:~~

~~(A) areas exceeding 100 contiguous square feet where timber operations have exposed bare soil,~~

Comment [p17]: Old T/I subsection 916.9(n) deleted.

Formatted: Highlight

1 ~~(B) approaches to tractor road watercourse crossings~~  
 2 ~~between the drainage facilities closest to the crossing,~~  
 3 ~~(C) road cut banks and fills, and (D) (C) any other area~~  
 4 ~~of disturbed soil that threatens to discharge sediment into waters in~~  
 5 ~~amounts deleterious to the quality and beneficial uses of water, may~~  
 6 ~~include, but need not be limited to, mulching, rip rapping, grass~~  
 7 ~~seeding, or chemical soil stabilizers. Where straw, mulch, or slash~~  
 8 ~~is used, the minimum coverage shall be 90%, and any treated area that~~  
 9 ~~has been subject to reuse or has less than 90% surface cover shall be~~  
 10 ~~treated again prior to the end of timber operations. The RPF may~~  
 11 ~~propose alternative treatments that will achieve the same level of~~  
 12 ~~erosion control and sediment discharge prevention.~~

Formatted: Highlight

13 ~~(4) (3) Where the undisturbed natural ground cover cannot~~  
 14 ~~effectively protect beneficial uses of water from timber operations,~~  
 15 ~~the ground shall be treated by measures including, but not limited to,~~  
 16 ~~seeding, mulching, or replanting, in order to retain and improve its~~  
 17 ~~natural ability to filter sediment, minimize soil erosion, and~~  
 18 ~~stabilize banks of watercourses and lakes.~~

19 (o) [No change]

20 (o) **Erosion Site identification and remedies-** As part of the plan , the RPF shall: **(1)**  
 21 Identify active erosion sites in the logging area, where erosion and sediment production are  
 22 ongoing during any period of the year and which pose significant risks to the beneficial uses of  
 23 water.

24 **(2)** Assess them those sites identified in 14 CCR § 916.9 [936.9, 956.9], subsection (o)  
 25 **(1)** to determine whether feasible remedies exist.

**Comment [p18]:** Retains the following existing recently adopted ASP rule subsection 916.9(o) to address identification and feasible mitigation of sites, unrelated to roads, landings and logging road watercourse crossings (e.g., tractor roads, diversions), where erosion and sediment production is ongoing and poses significant risks to water quality. Such "high risk sites" related to logging roads and landings are addressed under proposed 923.2(f).

1 ~~(3) and address in the planned feasible remediation for all sites that pose significant~~  
2 ~~wristed beneficial uses of water For sites that pose significant risks to the beneficial uses of~~  
3 ~~water and where feasible remedies exist, the plan shall propose appropriate treatment.~~

4 (p) **Section reserved for future use.**

5  
6 ~~(p) The erosion control maintenance period on permanent and seasonal~~  
7 ~~roads and associated landings that are not abandoned in accordance~~  
8 ~~with 14 CCR § 923.8 [943.8, 963.8] shall be three years.~~

9 ~~(q) (pq)~~ Site preparation activities shall be designed to prevent  
10 soil disturbance within, and minimize soil movement into, the channels  
11 of watercourses. Prior to any broadcast burning, burning  
12 prescriptions shall be designed to prevent loss of large woody debris  
13 in watercourses, and vegetation and duff within a WLPZ, or within any  
14 ELZ or EEZ designated for watercourse or lake protection. No ignition  
15 is to occur within any WLPZ, or within any ELZ or EEZ designated for  
16 watercourse or lake protection. When burning prescriptions are  
17 proposed, the measures or burning restrictions which are intended to  
18 accomplish this goal shall be stated in the plan and included in any  
19 required burning permit. This information shall be provided in  
20 addition to the information required under 14 CCR § 915.4 [935.4,  
21 955.4].

22 (r) **Water drafting - See 14 CCR § 923.7 [943.7, 963.7] subsection (k) (2). Water**  
23 ~~drafting for timber operations shall:~~

24 ~~(1) Comply with Fish and Game Code Section 1600, et seq.~~

25 ~~(A) Timber operations conducted under a Fish and Game Code Section 1600~~  
~~master or long term agreement that includes water drafting may provide proof of such coverage~~

**Comment [p19]:** See comment regarding the deletion of subsection (p) below (p14). An alternative to reshuffling all subsequent rule sections would be to duplicate what current 916.9 (i) states: "Section reserved for future use".

**Comment [p20]:** Removes existing ASP subsection 916.9(p) requiring a three year prescribed maintenance period for logging roads and landings and moves it to 923.7(1)(2) [943.7(1)(2), 963.7(1)(2)]

**Comment [p21]:** The ASP rules substantially revised 916.9(r) addressing water drafting for timber operations. A reference is provided here and the actual requirements in 923.7(k)2).

1 ~~for compliance with this paragraph.~~

2 ~~\_\_\_\_\_ (2) Describe the water drafting site conditions and proposed water drafting activity in the~~  
3 ~~plan, including:~~

4 ~~\_\_\_\_\_ (A) a general description of the conditions and proposed water drafting;~~

5 ~~\_\_\_\_\_ (B) a map showing proposed water drafting locations;~~

6 ~~\_\_\_\_\_ (C) the watercourse classification;~~

7 ~~\_\_\_\_\_ (D) the drafting parameters including the months the site is proposed for use;~~

8 ~~estimated total volume needed per day; estimated maximum instantaneous drafting rate and~~  
9 ~~filling time; and disclosure of other water drafting activities in the same watershed;~~

10 ~~\_\_\_\_\_ (E) the estimated drainage area (acres) above the point of diversion;~~

11 ~~\_\_\_\_\_ (F) the estimated unimpeded streamflow, pumping rate, and drafting duration;~~

12 ~~\_\_\_\_\_ (G) a discussion of the effects on aquatic habitat downstream from the drafting~~  
13 ~~site(s) of single pumping operations, or multiple pumping operations at the same location, and~~  
14 ~~at other locations in the same watershed;~~

15 ~~\_\_\_\_\_ (H) a discussion of proposed alternatives and measures to prevent adverse~~  
16 ~~effects to fish and wildlife resources, such as reducing hose diameter; using gravity fed tanks~~  
17 ~~instead of truck pumping; reducing the instantaneous or daily intake at one location; describing~~  
18 ~~allowances for recharge time; using other dust palliatives; and drafting water at alternative sites;~~  
19 ~~and \_\_\_\_\_~~

20 ~~\_\_\_\_\_ (I) The methods that will be used to measure source streamflow prior to the~~  
21 ~~water drafting operation and the conditions that will trigger streamflow to be measured during~~  
22 ~~the operation.~~

23 ~~\_\_\_\_\_ (3) All water drafting for timber operations are subject to each requirement below unless~~  
24 ~~the Department of Fish and Game modifies the requirement in the Lake or Streambed Alteration~~  
25 ~~agreement that authorized the drafting operation, or unless otherwise specified below:~~

1 ~~(A) All intakes shall be screened to prevent impingement of juvenile fish against~~  
2 ~~the screen. The following requirements apply to screens and water drafting on Class I waters:~~

3 ~~1. Openings in perforated plate or woven wire mesh screens shall not~~  
4 ~~exceed 3/32 inches (2.38 millimeters). Slot openings in wedge wire screens shall not exceed~~  
5 ~~1/16 inches (1.75 millimeters).~~

6 ~~2. The screen surface shall have at least 2.5 square feet of openings~~  
7 ~~submerged in water.~~

8 ~~3. The drafting operator shall regularly inspect, clean, and maintain~~  
9 ~~screens to ensure proper operation whenever water is drafted.~~

10 ~~4. The approach velocity (water moving through the screen) shall not~~  
11 ~~exceed 0.33 feet/second.~~

12 ~~5. The diversion rate shall not exceed 350 gallons per minute.~~

13 ~~(B) Approaches and associated drainage features to drafting locations within a~~  
14 ~~WLPZ or channel zone shall be surfaced with rock or other suitable material to minimize~~  
15 ~~generation of sediment.~~

16 ~~(C) Barriers to sediment transport, such as straw waddles, logs, straw bales or~~  
17 ~~sediment fences, shall be installed outside the normal high water mark to prevent sediment~~  
18 ~~delivery to the watercourse and limit truck encroachment.—~~

19 ~~(D) Water drafting trucks parked on streambeds and floodplains shall use drip~~  
20 ~~pans or other devices such as absorbent blankets, sheet barriers or other materials as needed~~  
21 ~~to prevent soil and water contamination from motor oil or hydraulic fluid leaks.~~

22 ~~(E) Bypass flows for Class I watercourses shall be provided in volume sufficient~~  
23 ~~to avoid dewatering the watercourse and maintain aquatic life downstream, and shall conform to~~  
24 ~~the following standard:~~

25 ~~1. Bypass flows in the source stream during drafting shall~~

1 ~~be at least 2 cubic foot per second.~~

2 ~~2. Diversion rate shall not exceed 10 percent of the surface flow.~~

3 ~~3. Pool volume reduction shall not exceed 10 percent.~~

4 ~~(F) The drafting operator shall keep a log that records for each time water is~~  
5 ~~drafted, the date, total pumping time, pump rate, starting time, ending time, and volume~~  
6 ~~diverted. Logs shall be filed with the Department of Forestry and Fire Protection at the end of~~  
7 ~~seasonal operations and maintained with the plan record. This requirement may be modified in~~  
8 ~~the approved plan that covers the water drafting, but only with concurrence from the Department~~  
9 ~~of Fish and Game.~~

10 ~~(G) Before commencing any water drafting operation, the RPF and the drafting~~  
11 ~~operator shall conduct a pre-operations field review to discuss the water drafting measures in~~  
12 ~~the plan and/or Lake or Streambed Alteration Agreement.~~

14 ~~(r) (g) Water drafting for timber operations from within a channel~~  
15 ~~zone of a natural watercourse or from a lake shall conform with the~~  
16 ~~following standards:~~

17 ~~(1) The RPF shall incorporate into the THP:~~

18 ~~(A) a description and map of proposed water drafting~~  
19 ~~locations, .~~

20 ~~(B) The watercourse or lake classification, . and~~

21 ~~(C) The general drafting location use parameters (i.e.,~~  
22 ~~yearly timing, estimated total volume needed, estimated total uptake~~  
23 ~~rate and filling time, and associated water drafting activities from~~  
24 ~~other THPs).~~

Comment [p22]: Old deleted  
T/I subsection (r)  
requirements.

1 ~~(2) On Class I and Class II streams where the RPF has estimated~~  
2 ~~that:~~

3 ~~(A) Bypass flows are less than 2 cubic feet per second,~~

4 ~~or~~

5 ~~(B) Pool volume at the water drafting site would be~~  
6 ~~reduced by 10%, or~~

Formatted: Highlight

7 ~~(C) Diversion rate exceeds 350 gallons per minute, or~~

8 ~~(D) Diversion rate exceeds 10% of the above surface~~  
9 ~~flow;~~

10 ~~no water drafting shall occur unless the RPF prepares a water drafting~~  
11 ~~plan to be reviewed and, if necessary a stream bed alteration~~  
12 ~~agreement issued, by DFG and approved by the Director. The Director~~  
13 ~~may accept the project description and conditions portion of an~~  
14 ~~approved "Streambed Alteration Agreement" issued under the Fish and~~  
15 ~~Game Code (F&GC 1600 et seq.) which is submitted instead of the water~~  
16 ~~drafting plan described in 14 CCR § 916.9 [936.9, 956.9] (g)(1)(C)~~  
17 ~~and (g)(2)(D)(1-5).~~

18 ~~The water drafting plan shall include, but not be limited to:~~

19 ~~1. Disclosure of estimated percent streamflow~~  
20 ~~reduction and duration of reduction;~~

21 ~~2. Discussion of the effects of single pumping~~  
22 ~~operations, or multiple pumping operations at the same location;~~

23 ~~3. Proposed alternatives and discussion to prevent~~  
24 ~~adverse effects (e.g. reduction in hose diameter, reduction in total~~  
25 ~~intake at one location, described allowances for recharge time, and~~  
~~alternative water drafting locations);~~

1 ~~4. eConditions for operators to include an~~  
2 ~~operations log kept on the water truck containing the following~~  
3 ~~information: Date, Time, Pump Rate, Filling Time, Screen Cleaned,~~  
4 ~~Screen Conditions, and Bypass flow observations,.~~

5 ~~5. aA statement by the RPF for a pre-operations~~  
6 ~~field review with the operator to discuss the conditions in the water~~  
7 ~~drafting plan.~~

8 ~~(3) Intakes shall be screened in Class I and Class II waters.~~  
9 ~~Screens shall be designed to prevent the entrainment or impingement of~~  
10 ~~all life stages of fish or amphibians. Screen specifications shall be~~  
11 ~~included in the plan.~~

12 ~~(4) Approaches to drafting locations within a WLPZ shall be~~  
13 ~~surfaced with rock or other suitable material to avoid generation of~~  
14 ~~sediment.~~

15 ~~(s) Exemption notices~~ No timber operations are allowed in a WLPZ,  
16 or within any ELZ or EEZ designated for watercourse or lake  
17 protection, under exemption notices except for:

- 18 (1) ~~H~~auling on existing roads~~.~~
- 19 (2) ~~R~~oad maintenance~~.~~
- 20 (3) ~~O~~perations conducted for public safety~~.~~
- 21 (4) ~~C~~onstruction or reconstruction of approved watercourse  
22 crossings~~.~~
- 23 (5) ~~T~~emporary crossings of dry Class III watercourses that do  
24 not require notification under Fish and Game Code § 1600 et seq. ~~or~~
- 25 (6) ~~H~~arvesting recommended in writing by DFG to address  
specifically identified forest conditions.

**Comment [p23]:** Retains existing (s) as adopted under the ASP rules for clarity (e.g., all exemption rules in Watersheds with Listed Anadromous Salmonids are found in one location). The ASP rules made non substantive changes (i.e., bulleted format, referencing specific DFG code section).

1 ~~(t)~~ **Emergency Notices** No timber operations are allowed in a WLPZ,  
2 or within any ELZ or EEZ designated for watercourse or lake  
3 protection, under emergency notices except for:

4 (1) ~~H~~auling on existing roads~~τ.~~

5 (2) ~~R~~oad maintenance~~τ.~~

6 (3) ~~O~~perations conducted for public safety~~τ.~~

7 (4) ~~C~~onstruction or reconstruction of approved watercourse  
8 crossings~~τ.~~

9 (5) ~~T~~emporary crossings of dry Class III watercourses that do  
10 not require notification under Fish and Game Code § 1600 et seq.

11 (6) ~~H~~arvesting recommended in writing by DFG to address  
12 specifically identified forest conditions~~τ.~~

13 (7) ~~T~~he harvest of dead or dying conifer trees subject to the  
14 following conditions:

15 (A) Retention of all trees in the core zone of Class I and  
16 Class II-L watercourses.

17 (B) Within any WLPZ, ELZ, or EEZ designated for Class II  
18 or III watercourse protection, a minimum of two dead, dying, or  
19 diseased conifer trees per acre at least 16 inches diameter breast  
20 high and 50 feet tall shall be retained within 50 feet of the  
21 watercourse transition line.

22 (C) Trees to be harvested or retained shall be marked by,  
23 or under the supervision of, an RPF prior to timber operations within  
24 the WLPZ or ELZ/EEZ.

25 (D) Within the WLPZ or ELZ/EEZ, if the stocking standards  
of 14 CCR § 912 [932, 952].7 are not met upon completion of timber

**Comment [p24]:** This subsection addresses operational limitations adjacent to watercourses under an emergency notice. The ASP rules made non-substantive changes (i.e., bulleted format, referencing specific DFG code section) and substantive changes (i.e., retention of trees within core zones).

1 operations, unless the area meets the definition of substantially  
2 damaged timberlands, at least ten trees shall be planted for each tree  
3 harvested but need not exceed an average point count of 300 trees per  
4 acre.

5 ~~(u)~~ **(u) Salvage logging** No salvage logging is allowed in a WLPZ  
6 without an approved HCP, a PTEIR, an SYP, or an approved plan that  
7 contains a section that sets forth objectives, goals, and measurable  
8 results for streamside salvage operations.

9 (1) This section does not apply to emergency operations under  
10 14 CCR § 1052.

11 ~~(v) (u) Nonstandard practices (i.e., waivers, exceptions, in lieu  
12 practices, and alternative practices) shall comply with the goal set  
13 forth in subsection (a) above as well as with the other requirements  
14 set forth in the rules.~~

**Comment [p25]:** Old deleted T/I rule.

15 ~~(w), (v) Site-specific measures or nonstandard provisions The Director  
16 may approve alternatives provided the alternative practice will  
17 achieve the goal of this section. The Director shall not accept for  
18 inclusion in a plan any alternative practice as described in this  
19 section where two or more agencies listed in 4582.6 of the PRC and 14  
20 CCR § 1037.3 have submitted written comments which lead to the  
21 Director's conclusion that the proposed alternative will not meet the  
22 goal of this section and the agency(ies) participated in the review of  
23 the plan, including an on-the-ground inspection.~~

**Comment [p26]:** NO change to this recently adopted ASP subsection (current rule language is not duplicated here).

**Formatted:** No underline

24 ~~(x)~~ **(w)** Except when expressly required by 14 CCR § 916.9 [936.9, 956.9],  
25 subsections (w)(1)-(5) below, the provisions of 14 CCR § 916.9 [936.9, 956.9] shall not

1 apply to a plan that is subject to an incidental take permit based upon an approved  
2 Habitat Conservation Plan that addresses anadromous salmonid protection.

3 (1) a valid incidental take permit issued by DFG pursuant to Section 2081(b) of the Fish  
4 and Game Code that addresses anadromous salmonid protection; or

5 (2) a federal incidental take statement or incidental take permit that addresses  
6 anadromous salmonid protection, for which a consistency determination has been made  
7 pursuant to Section 2080.1 of the Fish and Game Code; or

8 (3) a valid natural community conservation plan that addresses anadromous salmonid  
9 protection approved by DFG under section 2835 of the Fish and Game Code; or

10 (4) a valid Habitat Conservation Plan that addresses anadromous salmonid  
11 protection, approved under Section 10 of the federal Endangered Species Act of 1973;

12 or

13 (5) project revisions, guidelines, or take avoidance measures pursuant to a  
14 memorandum of understanding or a planning agreement entered into between the plan  
15 submitter and DFG in preparation of obtaining a natural community conservation plan  
16 that addresses anadromous salmonid protection.

**Comment [p27]:** No change to this ASP revised subsection. This subsection would also be reiterated as a new subsection 923(e) under the intent section of revised Article 12 Logging Roads and Landings [Article 11, Northern].

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

**Amend 918.3, 938.3, 958.3. ~~Roads to be Kept Passable~~**

~~Timber operators shall keep all logging truck roads in a passable condition during the dry season for fire truck travel until snag and slash disposal has been completed.~~

**Comment [p28]:** Removes subsection 918.3 [938.3, 958.3] and moves it to 923.6(d) [943.6(d), 963.6(d)], and changes period when applies to better match 918 [938, 958]

**Amend Articles 11 and 12 ~~Logging Roads and Landings~~ Logging Roads, Landings, and Logging Road Watercourse Crossings**

~~**Article 11 Logging Roads and Landings**~~

~~**Article 12 Logging Roads and Landings**~~

~~**923, 943, 963 Logging Roads and Landings**~~

~~All logging roads and landings in the logging area shall be planned, located, constructed, reconstructed, used, and maintained in a manner which: is consistent with long term enhancement and maintenance of the forest resource; best accommodates appropriate yarding systems, and economic feasibility; minimizes damage to soil resources and fish and wildlife habitat; and prevents degradation of the quality and beneficial uses of water. The provisions of this article shall be applied in a manner which complies with this standard.~~

~~Factors that shall be considered when selecting feasible alternatives (see 14 CCR 897 and 898) shall include, but are not limited to, the following:~~

- ~~(a) Use of existing roads whenever feasible.~~

1 ~~(b) Use of systematic road layout patterns to minimize total mileage.~~

2 ~~(c) Planned to fit topography to minimize disturbance to the natural~~  
3 ~~features of the site.~~

4 ~~(d) Avoidance of routes near the bottoms of steep and narrow canyons,~~  
5 ~~through marshes and wet meadows, on unstable areas, and near~~  
6 ~~watercourses or near existing nesting sites of threatened or~~  
7 ~~endangered bird species.~~

8 ~~(e) Minimization of the number of watercourse crossings.~~

9 ~~(f) Location of roads on natural benches, flatter slopes and areas of~~  
10 ~~stable soils to minimize effects on watercourses.~~

11 ~~(g) Use of logging systems which will reduce excavation or placement~~  
12 ~~of fills on unstable areas.~~

13  
14 ~~923.1, 943.1, 963.1 Planning for Roads and Landings [All Districts]~~

15 ~~The following standards for logging roads and landings shall be~~  
16 ~~adhered to:~~

17 ~~(a) All logging roads shall be located and classified on the THP map~~  
18 ~~as permanent, seasonal, or temporary. Road failures on existing roads~~  
19 ~~which will be reconstructed shall also be located on the THP map. In~~  
20 ~~addition to the requirements of 14 CCR 1034(x), the probable location~~  
21 ~~of those landings which require substantial excavation or which exceed~~  
22 ~~one quarter acre in size, shall be shown on the THP map.~~

23 ~~(b) New logging roads shall be planned in accordance with their~~  
24 ~~classification and maintenance requirements.~~

25 ~~(c) Logging roads and landings shall be planned and located, when~~  
~~feasible, to avoid unstable areas. The Director shall approve an~~

1 ~~exception if those areas are unavoidable, and site specific measures~~  
2 ~~to minimize slope instability due to construction are described and~~  
3 ~~justified in the THP.~~

4 ~~(d) Where roads and landings will be located across 100 feet or more~~  
5 ~~of lineal distance on any slopes over 65% or on slopes over 50% which~~  
6 ~~are within 100 ft. of the boundary of a WLPZ, measures to minimize~~  
7 ~~movement of soil and the discharge of concentrated surface runoff~~  
8 ~~shall be incorporated in the THP. The Director may waive inclusion of~~  
9 ~~such measures where the RPF can show that slope depressions, drainage~~  
10 ~~ways, and other natural retention and detention features are~~  
11 ~~sufficient to control overland transport of eroded material. The~~  
12 ~~Director may require end-hauling of material from areas within 100 ft.~~  
13 ~~of the boundary of a WLPZ to a stable location if end-hauling is~~  
14 ~~feasible and is necessary to protect water quality. The Director~~  
15 ~~shall require maintenance provisions in the THP for drainage~~  
16 ~~structures and facilities provided that such maintenance is feasible~~  
17 ~~and necessary to keep roadbeds and fills stable.~~

18 ~~(e) New logging roads shall not exceed a grade of 15% except that~~  
19 ~~itches of up to 20% shall be allowed not to exceed 500 continuous~~  
20 ~~feet (152.4 m). These percentages and distances may be exceeded only~~  
21 ~~where it can be explained and justified in the THP that there is no~~  
22 ~~other feasible access for harvesting of timber or where in the~~  
23 ~~Northern or Southern Districts use of a gradient in excess of 20% will~~  
24 ~~serve to reduce soil disturbance.~~

1 ~~(f) Roads and landings shall be planned so that an adequate number of~~  
2 ~~drainage facilities and structures are installed to minimize erosion~~  
3 ~~on roadbeds, landing surfaces, sidecast and fills.~~

4 ~~(g) Unless exceptions are explained and justified in the THP, general~~  
5 ~~planning requirements for roads shall include:~~

6 ~~(1) Logging roads shall be planned to a single lane width~~  
7 ~~compatible with the largest type of equipment used in the harvesting~~  
8 ~~operation with turnouts at reasonable intervals.~~

9 ~~(2) Roads shall be planned to achieve as close a balance~~  
10 ~~between cut volume and fill volume as is feasible.~~

11 ~~(3) When roads must be planned so that they are insloped and~~  
12 ~~ditched on the uphill side, drainage shall be provided by use of an~~  
13 ~~adequate number of ditch drains.~~

14 ~~(h) Road construction shall be planned to stay out of Watercourse and~~  
15 ~~Lake Protection Zones. When it is a better alternative for protection~~  
16 ~~of water quality or other forest resources, or when such roads are the~~  
17 ~~only feasible access to timber, exceptions may be explained and~~  
18 ~~justified in the THP and shall be agreed to by the Director if they~~  
19 ~~meet the requirements of this subsection.~~

20 ~~(i) [Coast] The location of all logging roads to be constructed~~  
21 ~~shall be flagged or otherwise identified on the ground before~~  
22 ~~submission of a THP or major amendment. Exceptions may be explained~~  
23 ~~and justified in the THP and agreed to by the Director if flagging is~~  
24 ~~unnecessary as a substantial aid to examining: (1) compatibility~~  
25 ~~between road location and yarding and silvicultural systems, or (2)~~  
~~possible significant adverse effects of road location on water~~

1 ~~quality, soil productivity, wildlife habitat, or other special~~  
2 ~~features of the area.~~

3 ~~(i) [Northern, Southern] All logging roads to be constructed shall~~  
4 ~~be flagged or otherwise identified on the ground before submission of~~  
5 ~~a THP or, substantial deviation, except for temporary roads less than~~  
6 ~~600 ft. in length that would meet the requirements for a minor~~  
7 ~~deviation (see 14 CCR 1036, 1039, 1040) if they were submitted as~~  
8 ~~such. Exceptions may be explained and justified in the THP and agreed~~  
9 ~~to by the Director if flagging or other identification is unnecessary~~  
10 ~~as a substantial aid to examining: (1) compatibility between road~~  
11 ~~location and yarding and silvicultural systems or (2) possible~~  
12 ~~significant adverse effects of road location on water quality, soil~~  
13 ~~productivity, wildlife habitat, or other special features of the area.~~

14 ~~(j) If logging roads will be used from the period of October 15 to~~  
15 ~~May 1, hauling shall not occur when saturated soil conditions exist on~~  
16 ~~the road.~~

17  
18 ~~**923.2, 943.2, 963.2 Road Construction [All Districts]**~~

19 ~~Logging roads shall be constructed or reconstructed in accordance with~~  
20 ~~the following requirements or as proposed by the RPF, justified in the~~  
21 ~~THP, and found by the Director to be in conformance with the~~  
22 ~~requirements of this Article.~~

23 ~~(a) Logging roads shall be constructed in accordance with the~~  
24 ~~approved THP. If a change in designation of road classification is~~  
25 ~~subsequently made, the change shall be reported in accordance with 14~~  
~~CCR 1039 or 1040, as appropriate.~~

1 ~~(b) Where a road section which is greater than 100 feet in length~~  
2 ~~crosses slopes greater than 65%, placement of fill is prohibited and~~  
3 ~~placement of sidecast shall be minimized to the degree feasible. The~~  
4 ~~Director may approve an exception where site specific measures to~~  
5 ~~minimize slope instability, soil erosion, and discharge of~~  
6 ~~concentrated surface runoff are described and justified in the THP.~~

7 ~~(c) On slopes greater than 50%, where the length of road section is~~  
8 ~~greater than 100 ft., and the road is more than 15 ft. wide (as~~  
9 ~~measured from the base of the cut slope to the outside of the berm or~~  
10 ~~shoulder of the road) and the fill is more than 4 ft. in vertical~~  
11 ~~height at the road shoulder for the entire 100 feet the road shall be~~  
12 ~~constructed on a bench that is excavated at the proposed toe of the~~  
13 ~~compacted fill and the fill shall be compacted. The Director may~~  
14 ~~approve exception to this requirement where on a site specific basis~~  
15 ~~if the RPF has described and justified an alternative practice that~~  
16 ~~will provide equal protection to water quality and prevention of soil~~  
17 ~~erosion.~~

18 ~~(d) [Coast] Fills, including through fills across watercourses shall~~  
19 ~~be constructed in a manner to minimize erosion of fill slopes using~~  
20 ~~techniques such as insloping through fill approaches, waterbars,~~  
21 ~~berms, rock armoring of fill slopes, or other suitable methods.~~

22 ~~(d) [Northern, Southern] Roads shall be constructed so no break in~~  
23 ~~grade, other than that needed to drain the fill, shall occur on~~  
24 ~~through fill; breaks in grade shall be above or below the through~~  
25 ~~fill, as appropriate. Where conditions do not allow the grade to~~

1 ~~break as required, through fills must be adequately protected by~~  
2 ~~additional drainage structures or facilities.~~

3 ~~(e) Through fills shall be constructed in approximately one foot~~  
4 ~~lifts.~~

5 ~~(f) On slopes greater than 35 percent, the organic layer of the soil~~  
6 ~~shall be substantially disturbed or removed prior to fill placement.~~

7 ~~The RPF may propose an exception in the THP and the Director may~~  
8 ~~approve the exception where it is justified that the fill will be~~  
9 ~~stabilized.~~

10 ~~(g) Excess material from road construction and reconstruction shall~~  
11 ~~be deposited and stabilized in a manner or in areas where downstream~~  
12 ~~beneficial uses of water will not be adversely affected.~~

13 ~~(h) Drainage structures and facilities shall be of sufficient size,~~  
14 ~~number and location to carry runoff water off of roadbeds, landings~~  
15 ~~and fill slopes. Drainage structures or facilities shall be installed~~  
16 ~~so as to minimize erosion, to ensure proper functioning, and to~~  
17 ~~maintain or restore the natural drainage pattern. Permanent~~  
18 ~~watercourse crossings and associated fills and approaches shall be~~  
19 ~~constructed where feasible to prevent diversion of stream overflow~~  
20 ~~down the road and to minimize fill erosion should the drainage~~  
21 ~~structure become plugged.~~

22 ~~(i) Where there is evidence that soil and other debris is likely to~~  
23 ~~significantly reduce culvert capacity below design flow, oversize~~  
24 ~~culverts, trash racks, or similar devices shall be installed in a~~  
25 ~~manner that minimizes culvert blockage.~~

1 ~~(j) Waste organic material, such as uprooted stumps, cull logs,~~  
2 ~~accumulations of limbs and branches, and unmerchantable trees, shall~~  
3 ~~not be buried in road fills. Wood debris or cull logs and chunks may~~  
4 ~~be placed and stabilized at the toe of fills to restrain excavated~~  
5 ~~soil from moving downslope.~~

6 ~~(k) Logging roads shall be constructed without overhanging banks.~~

7 ~~(l) Any tree over 12 inches (30.5 cm) d.b.h. with more than 25% of~~  
8 ~~the root surface exposed by road construction, shall be felled~~  
9 ~~concurrently with the timber operations.~~

10 ~~(m) Sidecast or fill material extending more than 20 ft. (6.1 m) in~~  
11 ~~slope distance from the outside edge of the roadbed which has access~~  
12 ~~to a watercourse or lake which is protected by a WLPZ shall be seeded,~~  
13 ~~planted, mulched, removed, or treated as specified in the THP, to~~  
14 ~~adequately reduce soil erosion.~~

15 ~~(n) All culverts at watercourse crossings in which water is flowing~~  
16 ~~at the time of installation shall be installed with their necessary~~  
17 ~~protective structures concurrently with the fill, construction and~~  
18 ~~reconstruction of logging roads. Other permanent drainage structures~~  
19 ~~shall be installed no later than October 15. For construction and~~  
20 ~~reconstruction of roads after October 15, drainage structures shall be~~  
21 ~~installed concurrently with the activity.~~

22 ~~(o) Drainage structures and drainage facilities on logging roads~~  
23 ~~shall not discharge on erodible fill or other erodible material unless~~  
24 ~~suitable energy dissipators are used. Energy dissipators suitable for~~  
25 ~~use with waterbreaks are described in 14 CCR 914.6(f) [934.6(f),~~  
~~954.6(f)].~~

1 ~~(p) Where roads do not have permanent and adequate drainage, the~~  
2 ~~specifications of Section 914.6 [934.6, 954.6] shall be followed.~~

3 ~~(q) Drainage facilities shall be in place and functional by October~~  
4 ~~15. An exception is that waterbreaks do not need to be constructed on~~  
5 ~~roads in use after October 15 provided that all such waterbreaks are~~  
6 ~~installed prior to the start of rain that generates overland flow.~~

7 ~~(r) No road construction shall occur under saturated soil conditions,~~  
8 ~~except that construction may occur on isolated wet spots arising from~~  
9 ~~localized ground water such as springs, provided measures are taken to~~  
10 ~~prevent material from significantly damaging water quality.~~

11 ~~(s) Completed road construction shall be drained by outsloping,~~  
12 ~~waterbreaks and/or cross draining before October 15. If road~~  
13 ~~construction takes place from October 15 to May 1, roads shall be~~  
14 ~~adequately drained concurrent with construction operations.~~

15 ~~(t) Roads to be used for log hauling during the winter period shall~~  
16 ~~be, where necessary, surfaced with rock in depth and quantity~~  
17 ~~sufficient to maintain a stable road surface throughout the period of~~  
18 ~~use. Exceptions may be proposed by the RPF, justified in the THP, and~~  
19 ~~found by the Director to be in conformance with the requirements of~~  
20 ~~this subsection.~~

21 ~~(u) Slash and other debris from road construction shall not be~~  
22 ~~bunched against residual trees which are required for silvicultural or~~  
23 ~~wildlife purposes, nor shall it be placed in locations where it could~~  
24 ~~be discharged into Class I or II watercourses.~~

25 ~~(v) Road construction activities in the WLPZ, except for stream~~  
~~crossings or as specified in the THP, shall be prohibited.~~

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

~~923.3, 943.3, 963.3 Watercourse Crossings [All Districts]~~

~~Watercourse crossing drainage structures on logging roads shall be planned, constructed, reconstructed, and maintained or removed, according to the following standards. Exceptions may be provided through application of Fish and Game Code Sections 1601 and 1603 and shall be included in the THP.~~

~~(a) The location of all new permanent watercourse crossing drainage structures and temporary crossings located within the WLPZ shall be shown on the THP map. If the structure is a culvert intended for permanent use, the minimum diameter of the culvert shall be specified in the plan. Extra culverts beyond those shown in the THP map may be installed as necessary.~~

~~(b) The number of crossings shall be kept to a feasible minimum.~~

~~(c) Drainage structures on watercourses that support fish shall allow for unrestricted passage of all life stages of fish that may be present, and shall be fully described in the plan in sufficient clarity and detail to allow evaluation by the review team and the public, provide direction to the LTO for implementation, and provide enforceable standards for the inspector.~~

~~(d) When watercourse crossings, other drainage structures, and associated fills are removed the following standards shall apply:~~

~~(1) Fills shall be excavated to form a channel that is as close as feasible to the natural watercourse grade and orientation, and that is wider than the natural channel.~~

1 ~~(2) The excavated material and any resulting cut bank shall be~~  
2 ~~sloped back from the channel and stabilized to prevent slumping and to~~  
3 ~~minimize soil erosion. Where needed, this material shall be~~  
4 ~~stabilized by seeding, mulching, rock armoring, or other suitable~~  
5 ~~treatment.~~

6 ~~(e) All permanent watercourse crossings that are constructed or~~  
7 ~~reconstructed shall accommodate the estimated 100 year flood flow,~~  
8 ~~including debris and sediment loads.~~

9 ~~(f) Permanent watercourse crossings and associated fills and~~  
10 ~~approaches shall be constructed or maintained to prevent diversion of~~  
11 ~~stream overflow down the road and to minimize fill erosion should the~~  
12 ~~drainage structure become obstructed. The RPF may propose an~~  
13 ~~exception where explained in the THP and shown on the THP map and~~  
14 ~~justified how the protection provided by the proposed practice is at~~  
15 ~~least equal to the protection provided by the standard rule.~~

16 ~~(g) Any new permanent culverts installed within class I watercourses~~  
17 ~~shall allow upstream and downstream passage of fish or listed aquatic~~  
18 ~~species during any life stage and for the natural movement of bedload~~  
19 ~~to form a continuous bed through the culvert and shall require an~~  
20 ~~analysis and specifications demonstrating conformance with the intent~~  
21 ~~of this section and subsection.~~

22 ~~(h) The amendments to 14 CCR § 923.3 [943.3, 963.3] that became~~  
23 ~~effective July 1, 2000 shall expire on December 31, 2007.~~

1  
2 ~~923.4, 943.4, 963.4 Road Maintenance [All Districts]~~

3 ~~Logging roads, landings, and associated drainage structures used in a~~  
4 ~~timber operation shall be maintained in a manner which minimizes~~  
5 ~~concentration of runoff, soil erosion, and slope instability and which~~  
6 ~~prevents degradation of the quality and beneficial uses of water~~  
7 ~~during timber operations and throughout the prescribed maintenance~~  
8 ~~period. In addition those roads which are used in connection with~~  
9 ~~stocking activities shall be maintained throughout their use even if~~  
10 ~~this is beyond the prescribed maintenance period.~~

11 ~~(a) The prescribed maintenance period for erosion controls on~~  
12 ~~permanent and seasonal roads and associated landings and drainage~~  
13 ~~structures which are not abandoned in accordance with 14 CCR 923.8~~  
14 ~~[943.8, 963.8] shall be at least one year. The Director may prescribe~~  
15 ~~a maintenance period extending up to three years in accordance with 14~~  
16 ~~CCR 1050.~~

17 ~~(b) Upon completion of timber operations, temporary roads and~~  
18 ~~associated landings shall be abandoned in accordance with 14 CCR 923.8~~  
19 ~~[943.8, 963.8].~~

20 ~~(c) Waterbreaks shall be maintained as specified in 14 CCR 914.6~~  
21 ~~[934.6, 954.6].~~

22 ~~(d) Unless partially blocked to create a temporary water source,~~  
23 ~~watercourse crossing facilities and drainage structures, where~~  
24 ~~feasible, shall be kept open to the unrestricted passage of water.~~  
25 ~~Where needed, trash racks or similar devices shall be installed at~~

1 ~~culvert inlets in a manner which minimizes culvert blockage.~~

2 ~~Temporary blockages shall be removed by November 15.~~

3 ~~(e) Before the beginning of the winter period, all roadside berms~~  
4 ~~shall be removed from logging roads or breached, except where needed~~  
5 ~~to facilitate erosion control.~~

6 ~~(f) Drainage structures, if not adequate to carry water from the~~  
7 ~~fifty year flood level, shall be removed in accordance with 14 CCR~~  
8 ~~923.3(d) [943.3(d), 963.3(d)] by the first day of the winter period,~~  
9 ~~before the flow of water exceeds their capacity if operations are~~  
10 ~~conducted during the winter period, or by the end of timber operations~~  
11 ~~whichever occurs first. Properly functioning drainage structures on~~  
12 ~~roads that existed before timber operations need not be removed. An~~  
13 ~~RPF may utilize an alternative practice, such as breaching of fill, if~~  
14 ~~the practice is approved by the Director as providing greater or equal~~  
15 ~~protection to water quality as removal of the drainage structure.~~

16 ~~(g) Temporary roads shall be blocked or otherwise closed to normal~~  
17 ~~vehicular traffic before the winter period.~~

18 ~~(h) During timber operations, road running surfaces in the logging~~  
19 ~~area shall be treated as necessary to prevent excessive loss of road~~  
20 ~~surface materials by, but not limited to, rocking, watering,~~  
21 ~~chemically treating, asphaltting or oiling.~~

22 ~~(i) Soil stabilization treatments on road or landing cuts, fills, or~~  
23 ~~sidecast shall be installed or renewed, when such treatment could~~  
24 ~~minimize surface erosion which threatens the beneficial uses of water.~~

25 ~~(j) Drainage ditches shall be maintained to allow free flow of water~~  
~~and minimize soil erosion.~~

1 ~~(k) Action shall be taken to prevent failures of cut, fill, or~~  
2 ~~sidecast slopes from discharging materials into watercourses or lakes~~  
3 ~~in quantities deleterious to the quality or beneficial uses of water.~~

4 ~~(l) Each drainage structure and any appurtenant trash rack shall be~~  
5 ~~maintained and repaired as needed to prevent blockage and to provide~~  
6 ~~adequate carrying capacity. Where not present, new trash racks shall~~  
7 ~~be installed if there is evidence that woody debris is likely to~~  
8 ~~significantly reduce flow through a drainage structure.~~

9 ~~(m) Inlet and outlet structures, additional drainage structures~~  
10 ~~(including ditch drains), and other features to provide adequate~~  
11 ~~capacity and to minimize erosion of road and landing fill and sidecast~~  
12 ~~to minimize soil erosion and to minimize slope instability shall be~~  
13 ~~repaired, replaced, or installed wherever such maintenance is needed~~  
14 ~~to protect the quality and beneficial uses of water.~~

15 ~~(n) Permanent watercourse crossings and associated approaches shall~~  
16 ~~be maintained to prevent diversion of stream overflow down the road~~  
17 ~~should the drainage structure become plugged. Corrective action shall~~  
18 ~~be taken before the completion of timber operations or the drainage~~  
19 ~~structure shall be removed in accordance with 14 CCR Section 923.3(d)~~  
20 ~~[943.3(d), 963.3(d)].~~

21 ~~(o) Except for emergencies and maintenance needed to protect water~~  
22 ~~quality, use of heavy equipment for maintenance is prohibited during~~  
23 ~~wet weather where roads or landings are within a WLPZ.~~

24 ~~(p) The Director may approve an exception to a requirement set forth~~  
25 ~~in subsections (b) through (o) above when such exceptions are~~  
~~explained and justified in the THP and the exception would provide for~~

1 ~~the protection of the beneficial uses of water or control erosion to a~~  
2 ~~standard at least equal to that which would result from the~~  
3 ~~application of the standard rule.~~

4  
5 ~~923.5, 943.5, 963.5 Landing Construction [All Districts]~~

6 ~~Landings shall be constructed according to the following standards:~~

7 ~~(a) On slopes greater than 65%, no fill shall be placed and sidecast~~  
8 ~~shall be minimized to the degree feasible. The Director may approve~~  
9 ~~an exception if, site specific measures to minimize slope instability,~~  
10 ~~soil erosion, and discharge of concentrated surface runoff are~~  
11 ~~described and justified in the THP.~~

12 ~~(b) On slopes greater than 50%, fills greater than 4 ft. in vertical~~  
13 ~~height at the outside shoulder of the landing shall be: 1)~~  
14 ~~constructed on a bench that is excavated at the proposed toe of the~~  
15 ~~fill and is wide enough to compact the first lift, and 2) compacted in~~  
16 ~~approximately 1 ft. lift from the toe to the finished grade. The RPF~~  
17 ~~or supervised designee shall flag the location of this bench or the~~  
18 ~~RPF shall provide a description of the bench location (narrative or~~  
19 ~~drawing) in the THP for fills meeting the above criteria, where the~~  
20 ~~length of landing section is greater than 100 feet. The RPF may~~  
21 ~~propose an exception in the THP and the Director may approve the~~  
22 ~~exception where it is justified that the landing will be stabilized.~~

23 ~~(c) Waste organic material, such as uprooted stumps cull logs,~~  
24 ~~accumulations of limbs and branches, or unmerchantable trees, shall~~  
25 ~~not be buried in landing fills. Wood debris or cull logs and chunks~~

1 ~~may be placed and stabilized at the toe of landing fills to restrain~~  
2 ~~excavated soil from moving downslope.~~

3 ~~(d) Constructed landings shall be the minimum in width, size, and~~  
4 ~~number consistent with the yarding and loading system to be used.~~

5 ~~Landings shall be no larger than one half acre (.202 ha) unless~~  
6 ~~explained and justified in the THP.~~

7 ~~(e) No landing construction shall occur under saturated soil~~  
8 ~~condition.~~

9 ~~(f) The following specifications shall be met upon completion of~~  
10 ~~timber operations for the year or prior to October 15, whichever~~  
11 ~~occurs first:~~

12 ~~(1) Overhanging or unstable concentrations of slash, woody~~  
13 ~~debris and soil along the downslope edge or face of the landings shall~~  
14 ~~be removed or stabilized when they are located on slopes over 65% or~~  
15 ~~on slopes over 50% within 100 ft. of a WLPZ.~~

16 ~~(2) Any obstructed ditches and culverts shall be cleaned.~~

17 ~~(3) Landings shall be sloped or ditched to prevent water from~~  
18 ~~accumulating on the landings. Discharge points shall be located and~~  
19 ~~designed to reduce erosion.~~

20 ~~(4) Sidecast or fill material extending more than 20 feet in~~  
21 ~~slope distance from the outside edge of the landing and which has~~  
22 ~~access to a watercourse or lake shall be seeded, planted, mulched,~~  
23 ~~removed or treated as specified in the THP to adequately reduce soil~~  
24 ~~erosion.~~

1 ~~(5) Sidecast or fill material extending across a watercourse~~  
2 ~~shall be removed in accordance with standards for watercourse crossing~~  
3 ~~removal set forth in 14 CCR 923.3 (d).~~

4 ~~(g) On slopes greater than 35%, the organic layer of the soil shall~~  
5 ~~substantially removed prior to fill placement.~~

6 ~~(h) When landings are constructed after October 15 they shall be~~  
7 ~~adequately drained concurrent with construction operations and shall~~  
8 ~~meet the requirements of (f)(1) through (f)(4) of this subsection upon~~  
9 ~~completion of operations at that landing.~~

10 ~~(i) The RPF may propose and the Director may approve waiver of~~  
11 ~~requirements in (f)(1) through (f)(4) of this subsection if the~~  
12 ~~Director finds they are not necessary to minimize erosion or prevent~~  
13 ~~damage to downstream beneficial uses. The Director may also approve an~~  
14 ~~exception to the October 15th date for treatment of slash and debris,~~  
15 ~~including the practice of burning.~~

16  
17 ~~923.6, 943.6, 963.6 Conduct of Operations on Roads and Landings [All~~  
18 ~~Districts]~~

19 ~~Routine use and maintenance of roads and landings shall not take place~~  
20 ~~when, due to general wet conditions, equipment cannot operate under~~  
21 ~~its own power. Operations may take place when roads and landings are~~  
22 ~~generally firm and easily passable or during hard frozen conditions.~~  
23 ~~Isolated wet spots on these roads or landings shall be rocked or~~  
24 ~~otherwise treated to permit passage. However, operations and~~  
25 ~~maintenance shall not occur when sediment discharged from landings or~~  
~~roads will reach watercourses or lakes in amounts deleterious to the~~

1 ~~quality and beneficial uses of water. This section shall not be~~  
2 ~~construed to prohibit activities undertaken to protect the road or to~~  
3 ~~reduce erosion.~~

4  
5 ~~**923.7, 943.7, 963.7 Licensed Timber Operator Responsibility for Roads**~~  
6 ~~**and Landings [All Districts]**~~

7 ~~The licensed timber operator who is responsible for the implementation~~  
8 ~~or execution of the plan shall not be responsible for the construction~~  
9 ~~and maintenance of roads and landings, unless the licensed timber~~  
10 ~~operator is employed for that purpose.~~

11  
12 ~~**923.8, 943.8, 963.8 Planned Abandonment of Roads, Watercourse**~~  
13 ~~**Crossings, and Landings [All Districts]**~~

14 ~~Abandonment of roads, watercourse crossings and landings shall be~~  
15 ~~planned and conducted in a manner which provides for permanent~~  
16 ~~maintenance free drainage, minimizes concentration of runoff, soil~~  
17 ~~erosion and slope instability, prevents unnecessary damage to soil~~  
18 ~~resources, promotes regeneration, and protects the quality and~~  
19 ~~beneficial uses of water. General abandonment procedures shall be~~  
20 ~~applied in a manner which satisfies this standard and include the~~  
21 ~~following:~~

22 ~~(a) Blockage of roads so that standard production four wheel drive~~  
23 ~~highway vehicles cannot pass the point of closure at the time of~~  
24 ~~abandonment.~~

1 ~~(b) Stabilization of exposed soil on cuts, fills, or sidecast where~~  
2 ~~deleterious quantities of eroded surface soils may be transported in a~~  
3 ~~watercourse.~~

4 ~~(c) Grading or shaping of road and landing surfaces to provide~~  
5 ~~dispersal of water flow.~~

6 ~~(d) Pulling or shaping of fills or sidecast where necessary to~~  
7 ~~prevent discharge of materials into watercourses due to failure of~~  
8 ~~cuts, fills, or sidecast.~~

9 ~~(e) Removal of watercourse crossings, other drainage structures, and~~  
10 ~~associated fills in accordance with 14 CCR 923.3(d). Where it is not~~  
11 ~~feasible to remove drainage structures and associated fills, the fill~~  
12 ~~shall be excavated to provide an overflow channel which will minimize~~  
13 ~~erosion of fill and prevent diversion of overflow along the road~~  
14 ~~should the drainage structure become plugged.~~

15 The Director may approve an exception to a requirement set forth in  
16 ~~(b) through (c) above when such exceptions are explained and justified~~  
17 ~~in the THP and the exception would provide for the protection of the~~  
18 ~~beneficial uses of water or control erosion to a standard at least~~  
19 ~~equal to that which would result from the application of the standard~~  
20 ~~rule.~~

21  
22 ~~**923.9, 943.9, 963.9 Roads and Landings in Watersheds with Threatened**~~  
23 ~~**or Impaired Values [All Districts]**~~

24 ~~— In addition to all other district Forest Practice Rules, the~~  
25 ~~following requirements shall apply in any planning watershed with~~  
~~threatened or impaired values:~~

1 ~~(a) Where logging road or landing construction or reconstruction is~~  
2 ~~proposed, the plan shall state the locations of and specifications for~~  
3 ~~road or landing abandonment or other mitigation measures to minimize~~  
4 ~~the adverse effects of long term site occupancy of the transportation~~  
5 ~~system within the watershed.~~

6 ~~(b) Unless prohibited by existing contracts with the U.S.D.A. Forest~~  
7 ~~Service or other federal agency, new and reconstructed logging roads~~  
8 ~~shall be no wider than a single lane compatible with the largest type~~  
9 ~~of equipment specified for use on the road, with adequate turnouts~~  
10 ~~provided as required for safety. The maximum width of these roads~~  
11 ~~shall be specified in the plan. These roads shall be outsloped where~~  
12 ~~feasible and drained with water breaks or rolling dips (where the road~~  
13 ~~grade is inclined at 7 percent or less), in conformance with other~~  
14 ~~applicable Forest Practice Rules.~~

15 ~~(c) The following shall apply on slopes greater than 50%:~~

16 ~~—— (1) Specific provisions of construction shall be identified and~~  
17 ~~described for all new roads.~~

18 ~~(2) Where cutbank stability is not an issue, roads may be~~  
19 ~~constructed as a full benched cut (no fill). Spoils not utilized in~~  
20 ~~road construction shall be disposed of in stable areas with less than~~  
21 ~~30 percent slope and outside of any WLPZ, EEZ, or ELZ.~~

22 ~~(3) Alternatively, roads may be constructed with balanced cuts~~  
23 ~~and fills if properly engineered, or fills may be removed with the~~  
24 ~~slopes recontoured prior to the winter period.~~

25 ~~(d) In addition to the provisions listed under 14 CCR 923.1(e)~~  
~~{943.1(e), 963.1(e)}, all permanent or seasonal logging roads with a~~

1 ~~grade of 15% or greater that extends 500 continuous feet or more shall~~  
2 ~~have specific erosion control measures stated in the plan.~~

3 ~~(e) Where situations exist that elevate risks to the values set forth~~  
4 ~~in 14 CCR 916.2(a), [936.2(a), 956.2(a)] (e.g., road networks are~~  
5 ~~remote, the landscape is unstable, water conveyance features~~  
6 ~~historically have a high failure rate, culvert fills are large)~~  
7 ~~drainage structures and erosion control features shall be oversized,~~  
8 ~~low maintenance, or reinforced, or they shall be removed before the~~  
9 ~~completion of the timber operation. The method of analysis and the~~  
10 ~~design for crossing protection shall be included in the plan.~~

11 ~~(f) The provisions of 14 CCR 923.9 [943.9, 963.9] shall not apply to~~  
12 ~~a plan that is subject to an incidental take permit based upon an~~  
13 ~~approved Habitat Conservation Plan that addresses anadromous salmonid~~  
14 ~~protection.~~

15 ~~(g) This section shall expire on December 31, 2007.~~

16  
17  
18  
19  
20  
21  
22  
23  
24  
25

1 923, 943, 963 Intent for Logging Roads, Landings, and Logging Road  
2 **Watercourse Crossings**

3  
4 (a) All logging roads, landings, and logging road watercourse  
5 crossings in the logging area shall be planned, constructed,  
6 reconstructed, used, maintained, removed, abandoned, and deactivated  
7 in a manner that:

8 (1) Is consistent with long-term enhancement and maintenance of  
9 the forest resource.

10 (2) Accommodates appropriate yarding systems.

11 (3) Is economically feasible.

12 (b) Such planning, construction, reconstruction, use, maintenance,  
13 removal, abandonment, and deactivation shall occur in a manner that  
14 minimizes potential adverse impacts to, among other things:

15 (1) Public safety.

16 (2) Fish and wildlife habitat.

17 (3) Water quality and the beneficial uses of water.

18 (4) Soil resources.

19 (5) Significant archeological and historical sites.

20 (6) Air quality.

21 (7) Visual resources.

22 (8) Worker safety.

23 (9) Fire hazard.

24 (c) The RPF may propose exceptions to these rules if explained and  
25 justified in the plan and found by the Director to be in conformance  
with this article.

Formatted: Highlight

1 (d) Exceptions ~~also~~ also be provided through application of Fish and  
2 Game Code Sections 1600 et seq. and shall be made an enforceable part  
3 of the plan in accordance with 14 CCR §§ 1039, 1040, 1090.14, 1092.26,  
4 or 1092.27, as appropriate.

Formatted: Highlight

5 (e) ~~The provisions of Article 12 that apply in watersheds with listed~~  
6 ~~anadromous salmonids threatened or impaired values shall not apply to a~~  
7 ~~plan that is subject to an approved Habitat Conservation Plan, Natural~~  
8 ~~Communities Conservation Plan, or Incidental Take Permit that addresses~~  
9 ~~anadromous salmonid protection.; an incidental take permit based upon an~~  
10 ~~approved Habitat Conservation Plan that addresses anadromous salmonid protection.~~

Comment [p29]: ASP revised subsection 916.9(w) requirements copied to here.

11 (1) a valid incidental take permit issued by DFG pursuant to Section 2081(b) of the Fish  
12 and Game Code that addresses anadromous salmonid protection; or

13 (2) a federal incidental take statement or incidental take permit that addresses  
14 anadromous salmonid protection, for which a consistency determination has been made  
15 pursuant to Section 2080.1 of the Fish and Game Code; or

16 (3) a valid natural community conservation plan that addresses anadromous  
17 salmonid protection approved by DFG under section 2835 of the Fish and Game Code;  
18 or

19 (4) a valid Habitat Conservation Plan that addresses anadromous salmonid  
20 protection, approved under Section 10 of the federal Endangered Species Act of 1973;

21 or

22 (5) project revisions, guidelines, or take avoidance measures pursuant to a  
23 memorandum of understanding or a planning agreement entered into between the plan  
24 submitter and DFG in preparation of obtaining a natural community conservation plan  
25 that addresses anadromous salmonid protection.

1 ~~(f) The provisions that apply in watersheds with threatened or~~  
2 ~~impaired values ~~that~~ expire on December 31, 2009.~~

Comment [p30]: Deleted due to permanent adoption of ASP rules.

Formatted: Highlight

3  
4 **923.1, 943.1, 963.1 Planning for Logging Roads and Landings**

5  
6 The following standards shall apply to logging roads and landings:

7 (a) Logging roads and landings shall be planned and located within  
8 the context of a systematic layout pattern that considers 14 CCR §  
9 923(b), uses existing logging roads and landings where feasible and  
10 appropriate, provides access for fire and resource protection  
11 activities, and minimizes the following:

12 (1) Total road mileage.

13 (2) The number of logging road watercourse crossings.

14 (3) Activities near watercourses, lakes, marshes, wet meadows,  
15 and other wet areas.

16 (4) Activities across steep areas that lead without flattening  
17 to Class I, II, III, or IV watercourses and lakes.

18 (5) Activities on unstable areas or in **connected headwall**  
19 swales.

20 (6) Activities near nesting sites of rare, threatened, or  
21 endangered bird species.

22 (7) Activities near significant populations of rare,  
23 threatened, or endangered plants.

24 (8) Ground disturbance, cuts, and fills.  
25

1 (9) The potential for affecting surface hydrology, including  
2 but not limited to, concentrating or diverting runoff or draining the  
3 logging road or landing surface directly into a watercourse or lake.

4 (10) Maintenance needs while being compatible with the logging  
5 road classification and long-term road usage.

6 (b) No logging roads or landings shall be planned for construction or  
7 reconstruction in Class I, II, III, or IV watercourses or lakes,  
8 within a WLPZ, or in marshes, wet meadows, and other wet areas, except  
9 as follows:

10 (1) At existing logging road watercourse crossings.

11 (2) At constructed or reconstructed logging road watercourse  
12 crossings approved as part of the Fish and Game Code process (F&GC  
13 1600 et seq.)

14 (3) At logging road watercourse crossings of Class III  
15 watercourses that are dry at the time of use.

16 (c) Logging roads and landings shall be planned and located to avoid  
17 unstable areas and **connected headwall swales**. The Director  
18 approve an exception if those areas are unavoidable and site-specific  
19 measures to minimize slope instability due to logging road or landing  
20 construction or reconstruction are described and justified in the  
21 plan.

22 (d) As part of the field examination of classified watercourses and  
23 lakes, the RPF or supervised designee shall evaluate areas in and near  
24 existing, constructed, and reconstructed logging roads and landings  
25 for sensitive conditions, including, but not limited to, unstable and  
erodible watercourse banks, unstable upslope areas, channels with

Formatted: Highlight

1 inadequate flow capacity, changeable channels, overflow channels,  
2 flood prone areas, debris jam potential, and riparian zones.

3 (1) The RPF shall consider these conditions and the measures  
4 needed to maintain and restore, to the extent feasible, the functions  
5 set forth in 14 CCR § 916.4(b) [936.4(b), 956.4(b)] when planning  
6 logging roads and landings.

7 (2) The plan shall identify such sensitive conditions,  
8 including where they ~~may~~ interact with proposed timber operations,  
9 that individually or cumulatively, significantly and adversely affect,  
10 the beneficial uses of water.

11 (3) The RPF shall describe in the plan feasible protection  
12 measures for identified sensitive conditions, which consider the  
13 watercourse classification and the location and planned use of all  
14 logging roads and landings.

15 (4) Where feasible protection measures are proposed, the RPF  
16 shall specify an implementation schedule in the plan.

17 (e) When selecting feasible alternatives (see 14 CCR §§ 897 and 898)  
18 during the planning phase of logging roads and landings, the RPF shall  
19 consider the location and planned use of logging roads and landings  
20 and whether such logging roads and landings ~~may~~ be abandoned or  
21 deactivated.

22 (f) Option 1: In watersheds with ~~threatened or impaired values~~ listed  
23 anadromous salmonids, where logging road or landing construction or  
24 reconstruction is proposed, the plan shall state the location of, and  
25 specifications for, logging road and landing abandonment or other

Formatted: Highlight

Formatted: Highlight

1 mitigation measures to minimize the adverse effects of long-term site  
2 occupancy of the road system within the watershed.

3 Option 2: In watersheds with listed anadromous salmonids threatened or  
4 impaired values, where logging road or landing construction or  
5 reconstruction is proposed, the plan shall identify:

6 (1) How the proposed operations will fit into the systematic  
7 layout pattern.

8 (2) What, if any, offsetting mitigation measures, including but  
9 not limited to, abandonment of logging roads and landings, are needed  
10 to minimize potential adverse impacts to watersheds from the road  
11 system.

12 (g) OPTION 1: In watersheds with protected anadromous salmonids, no  
13 roads or landings shall be planned for construction or reconstruction  
14 in a Channel Migration Zone or within the Inner Zones A and B of flood  
15 prone areas for Class I and Class II watercourses except as follows:

16 When feasible, use of existing roads and landings in flood prone areas  
17 shall be minimized in Inner Zones A and B. Exceptions include

18 (1) At existing logging road watercourse crossings.

19 (2) At constructed or reconstructed logging road watercourse  
20 crossings approved as part of the Fish and Game Code process (F&GC  
21 1600 et seq.)

22 (3) At logging road watercourse crossings of Class III  
23 watercourses that are dry at the time of use.

24 (4) Where the use of roads and landings to accomplish actions  
25 to improve salmonid habitat conditions stated in 14 CCR § 916.9

[936.9, 956.9]. subsection (f)(3)(E)(1.)

Comment [p31]: Current ASP rule language of 923.9(a)

Comment [p32]: Option 2: Requires identifying rationale for new roads and measures as needed to minimize impacts. The RRTF believes this subsection should be re-visited.

Formatted: Highlight

Comment [p33]: SPITTLER-Option 1 to address ASP channel migration zone rule 916,9(f)(3)(A) and flood prone area/Preferred Management Practices rule (E)4 under a combined planning requirement.

1 OPTION 2: (g) In watersheds with listed anadromous salmonids no  
2 logging roads or landings shall be planned for construction or  
3 reconstruction in the channel migration zone of a Class I watercourse  
4 except those listed in 14 CCR § 916.9 [936.9, 956.9], subsection  
5 (e) (1) (A)-(E) or pursuant to 14 CCR § 916.9 [936.9, 956.9] subsection  
6 (v).

7 (h) In watersheds with listed anadromous salmonids within the inner  
8 zone A and B of flood prone areas of Class I watercourses the  
9 following Preferred Management Practices should be considered for  
10 inclusion in the plan by the RPF and by the Director:

11 (1) No constructed and reconstructed logging roads and landings  
12 shall planned for location within these zones.

13 (2) When feasible, minimize use of existing logging roads and  
14 landings in the flood prone area.

15 (3) Exceptions include the use of roads and landings to  
16 accomplish actions to improve salmonid habitat conditions stated in 14  
17 CCR § 916.9 [936.9, 956.9], subsection (f) (3) (E) (1).

18  
19  
20 **923.2, 943.2, 963.2 Design and Implementation for Logging Roads and**  
21 **Landings**

22  
23 Constructed and reconstructed logging roads and landings shall be  
24 designed and implemented in accordance with their proposed use,  
25 maintenance requirements, and the approved plan:

(a) Constructed and reconstructed logging roads and landings shall:

**Comment [p34]:** RIBAR-Option 2 to address ASP rule 916,9(f)(3)(A) and (E)4 separately under planning. Option 2 is separated into two subsections (g) and (h) as they have different limitations and requirements.

1 (1) Avoid or mitigate potential impacts to public safety.

2 (2) Avoid unstable areas and **connected headwall swales** and  
3 minimize activities that adversely affect them.

4 (3) Minimize cuts and fills to the extent feasible.

5 (4) Be outsloped where feasible and drained with waterbreaks or  
6 rolling dips in conformance with other applicable Forest Practice  
7 Rules.

8 (5) Include adequate drainage structures and facilities  
9 necessary to avoid concentrating and diverting runoff, to minimize  
10 erosion of roadbeds, landing surfaces, drainage ditches, sidecast and  
11 fills, to minimize the potential for soil erosion and sediment  
12 transport, and to prevent the discharge of sediment into watercourses  
13 and lakes in **quantities deleterious** to the beneficial uses of water.

14 (6) Avoid crossing, or locations on, 100 feet or more of lineal  
15 distance over any slopes greater than 65 percent or within 100 feet of  
16 the boundary of a WLPZ on slopes greater than 50 percent that drain  
17 toward the zoned watercourse or lake. Where logging road or landing  
18 construction or reconstruction is necessary in these areas, specific  
19 measures to minimize movement of soil and the discharge of  
20 concentrated surface runoff shall be incorporated in the plan. The  
21 Director **may** waive inclusion of such measures where the RPF can show  
22 that slope depressions, drainage ways, and other natural retention and  
23 detention features are sufficient to control overland transport of  
24 eroded material.

**Comment [p35]:** The RRTF established this statewide requirement based on portions of ASP rule 923.9 (b) and after considering this and other performance standards removed the "(where the road grade is inclined at 7 percent or less)" for ASP watersheds.

**Formatted:** Highlight

**Formatted:** Highlight

1 (b) The Director ~~may~~ require removal of deposits of excess material  
2 if the deposits are in a position to adversely affect the beneficial  
3 uses of water and if the removal of the material is feasible.

Formatted: Highlight

4 (c) Excess material excavated during logging road and landing  
5 construction shall not be transported to disposal sites where it ~~will~~  
6 discharge into a watercourse or lake in ~~quantities deleterious~~ to the  
7 beneficial uses of water.

Formatted: Highlight

Formatted: Highlight

8 (d) In addition to the requirements of subsection (a) above, all  
9 constructed and reconstructed logging roads shall:

10 (1) Be no wider than a single-lane compatible with the largest  
11 type of equipment specified for use on the logging road, with adequate  
12 turnouts provided as required for safety unless prohibited by existing  
13 contracts with the U.S.D.A. Forest Service or other federal agency.

14 (2) Avoid grades greater than 20% or grades greater than 15%  
15 that extend greater than 500 continuous feet. Exceptions ~~may~~ be  
16 approved where there is no other feasible access for harvesting of  
17 timber or where use of a gradient greater than 20% ~~will~~ serve to  
18 reduce soil disturbance.

Formatted: Highlight

Formatted: Highlight

19 (e) In addition to the requirements of subsection (a) above, all  
20 constructed and reconstructed landings shall:

21 (1) Be consistent with the yarding and loading system to be  
22 used.

23 (2) Be no larger than one-half acre.

24 (3) Avoid construction on slopes greater than 40 percent where  
25 the landing ~~will~~ exceed one-quarter acre in size.

Formatted: Highlight

**Comment [p36]:** Change is consistent with the requirements of recently adopted ASP rule 916.9(o).

1 ~~(f)~~ In watersheds with ~~threatened or impaired values~~ listed anadromous  
2 salmonids, as part of the plan the RPF shall:

3 ~~(1) Identify logging road and landing active erosion sites in~~  
4 ~~the logging area, where erosion and sediment production are ongoing~~  
5 ~~during any period of the year and which pose significant risks to the~~  
6 ~~beneficial uses of water associated with logging roads and landings in~~  
7 ~~the harvest area and along logging roads owned or controlled by the~~  
8 ~~timber owner, timberland owner, plan submitter, or timber operator~~  
9 ~~that are used for timber operations under the plan.~~

10 ~~(2) Assess such those sites identified in 14 CCR § 923.2 [943.2,~~  
11 ~~963.2], subsection (f)(1) to determine whether feasible remedies~~  
12 ~~exist which ones pose significant risks to the beneficial uses of~~  
13 ~~water.~~

14 ~~(3) For Assess those sites, which that~~ pose significant risks  
15 to the beneficial uses of water, ~~and where to determine whether~~  
16 ~~feasible remedies exist, the plan shall propose appropriate treatment.~~

17 ~~(4) For sites that pose significant risks to the beneficial~~  
18 ~~uses of water and where feasible remedies exist, the plan shall~~  
19 ~~propose appropriate treatment.~~

20  
21 923.3, 943.3, 963.3 Mapping and Identification for Logging Roads and  
22 Landings

23  
24 The following mapping and identification standards shall apply to  
25 logging roads and landings:

1 (a) For logging road- and landing-related mapping requirements refer  
2 to 14 CCR §§ 1034(x)(4)(A)-(B) and (5)(A)-(K), 1090.5(w)(4)-(6),  
3 1090.5(hh), 1090.7(n)(4)-(6), and 1092.09(1)(5)(A)-(B) and (6)(A)-(K).

4 (b) For logging road- and landing-related disclosure and description  
5 requirements refer to 14 CCR §§ 1034(ii)(1)-(18), 1034(jj)(1)-(2), and  
6 1090.5(gg).

7 (c) For logging road- and landing-related identification requirements  
8 refer to 14 CCR § 1034(hh).

9 (d) The RPF shall identify in the field all constructed and  
10 reconstructed logging roads and landings:

11 (1) Across slopes greater than 65 percent for 100 lineal feet  
12 or more.

13 (2) Across slopes greater than 50 percent for 100 lineal feet  
14 or more within 100 feet of the boundary of a WLPZ that drains toward  
15 the zoned watercourse or lake.

16 (e) The location of all logging roads to be constructed or  
17 reconstructed shall be flagged or otherwise identified on the ground

18 Option 1: before submission of a plan or substantial deviation (Option

19 2: prior to the pre-harvest inspection, if necessary, or prior to

20 logging road construction or reconstruction). Exceptions § 1 be  
21 explained and justified in the plan and agreed to by the Director if

22 flagging is unnecessary as a substantial aid to examining: (1)

23 compatibility between logging road location and yarding and

24 silvicultural systems, or (2) possible significant adverse effects of

25 logging road location on the factors listed under 14 CCR § 923(b)

[943(b), 963(b)].

Formatted: Highlight

1  
2 923.4, 943.4, 963.4 Construction and Reconstruction for Logging Roads  
3 and Landings

4  
5 Logging roads and landings shall be constructed or reconstructed in  
6 accordance with the approved plan and the following requirements. If  
7 a change in designation of logging road classification is made after  
8 the plan is approved, the change shall be reported in accordance with  
9 14 CCR §§ 1039, 1040, 1090.14, 1092.26 or 1092.27, as appropriate.

10 (a) Logging roads and landings shall not be constructed or  
11 reconstructed where such operations pose a significant risk to public  
12 safety.

13 (b) Logging roads or landings shall not be constructed or  
14 reconstructed in Class I, II, III, or IV watercourses or lakes, the  
15 WLPZ, marshes, wet meadows, or other wet areas, except for logging  
16 road watercourse crossings or as specified in the plan.

17 (c) Logging roads and landings shall not be constructed or  
18 reconstructed across unstable areas or **connected headwall swales.**

19 (d) Logging roads and landings shall not be constructed with  
20 overhanging banks.

21 (e) Any tree over 12 inches dbh with more than 25 percent of the root  
22 surface exposed by logging road or landing construction shall be  
23 felled concurrently with the timber operations.

24 (f) On slopes greater than 40 percent, the organic layer of the soil  
25 shall be removed prior to fill placement.

1 (g) Waste organic material, such as uprooted stumps, cull logs,  
2 accumulations of limbs and branches, and unmerchantable trees, shall  
3 not be buried in logging road or landing fills. Wood debris or cull  
4 logs and chunks **may** be placed and stabilized at the toe of fill to  
5 restrain excavated soil from moving downslope.

Formatted: Highlight

6 (h) Slash and other debris from road construction shall not be  
7 bunched against residual trees, which are required for silvicultural  
8 or wildlife purposes, nor shall it be placed in locations where it  
9 **could** be discharged into Class I or II watercourses or lakes.

10 (i) Where **constructed** fills **fill** exceed three feet in vertical  
11 thickness, fill slopes shall be inclined no greater than 65 percent.

Comment [p37]: Optional addition. I believe Tom Spittler suggested this to improve clarity at the 11/10/09 RRTF meeting?

Formatted: Highlight

12 (j) Logging roads or landings shall not be constructed or  
13 reconstructed under saturated soil conditions, except that  
14 construction **may** occur on isolated wet spots arising from localized  
15 ground water such as springs, provided measures are taken to minimize  
16 soil erosion and sediment transport and to prevent the discharge of  
17 sediment into watercourses and lakes in **quantities deleterious** to the  
18 beneficial uses of water.

Formatted: Highlight

Formatted: Highlight

19 (k) Construction or reconstruction of logging roads or landings shall  
20 not take place during the winter period unless the approved plan  
21 incorporates a complete winter period operating plan pursuant to 14 §  
22 CCR 914.7(a) [934.7(a), 954.7(a)] that specifically addresses such  
23 logging road or landing construction or reconstruction.

24 (l) On slopes greater than 50 percent for greater than 100 lineal  
25 feet, fills greater than four feet in vertical height at the outside  
shoulder of the logging road or landing shall be:

1 (1) Constructed on a bench that is excavated at the proposed toe  
2 of the fill and is wide enough to compact the first lift.

3 (2) Compacted in approximately one-foot lifts from the toe to the  
4 finished grade or retained by an engineered structure.

5 (m) Logging roads and landings shall not be constructed or  
6 reconstructed across 100 feet or more of lineal distance on any slope  
7 greater than 65 percent or within 100 feet of the boundary of a WLPZ  
8 on slopes greater than 50 percent that drain toward the zoned  
9 watercourse or lake unless specific construction techniques or  
10 measures are described in the plan.

11 (n) Fills shall not be constructed on slopes greater than 65 percent.

12 (o) On slopes greater than 65 percent, sidecast from logging road and  
13 landing construction shall be minimized to the degree feasible.

14 (p) Excess material transported from logging road or landing  
15 construction or reconstruction shall be deposited and stabilized in a  
16 manner and in areas that avoid potential adverse impacts to:

17 (1) Public safety.

18 (2) Areas that could deliver sediment into a watercourse or  
19 lake in quantities deleterious to the quality and beneficial uses of  
20 water.

21 (q) Where conditions are encountered during logging road or landing  
22 construction or reconstruction that differ from what was anticipated  
23 during the preparation and review of the plan and that could result in  
24 a significant adverse impact on the environment or to public safety,  
25 the LTO shall inform the RPF or plan submitter of these unanticipated  
conditions in accordance with 14 CCR § 1035.3. If necessary, the

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

1 responsible RPF or plan submitter shall submit to the Director a  
2 deviation to the plan describing the unanticipated conditions and  
3 proposing appropriate actions.

4 ~~(r)~~ OPTION 1: In watersheds with protected anadromous salmonids, no  
5 new roads and landings shall be constructed within Channel Migration  
6 Zones or within Inner Zones A and B of flood prone areas.

**Comment [p38]:** SPITTLER-  
Option 1 to address ASP rule  
916,9(f)(3)(A) and (E)4  
under construction.

7  
8 OTION 2: (r) In watersheds with listed anadromous salmonids, no new  
9 roads and landings shall be constructed or reconstructed within the  
10 channel migration zone of a Class I watercourse except for those listed  
11 in 14 CCR § 916.9 [936.9,956.9], subsection (e)(1)(A)-(F) or pursuant to 14  
12 CCR § 916.9 [936.9, 956.9], subsection (v).

**Comment [p39]:** RIBAR-Option  
2 only addresses ASP channel  
migration zone rule  
916,9(f)(3)(A) under  
construction. ASP Preferred  
Management Measures  
916,9(f)(3)(E)4 is not  
addressed under construction  
as the rule relates to  
planning and is not a  
requirement.

13 ~~(rs)~~ In watersheds with ~~threatened or impaired values~~ listed anadromous  
14 salmonids, the following shall apply:

**Comment [p40]:** Consistent  
with planning requirement  
923.1(g). Proposed  
construction/reconstruction  
would require a site  
specific measure or  
nonstandard operational  
provision pursuant to  
916.9(v).

15 (1) On slopes greater than 50 percent that have access to a  
16 watercourse or lake:

**Comment [p41]:** Modified to  
reflect recently adopted ASP  
rules changes to 923.9(c).

17 (A) Specific provisions of construction shall be  
18 identified and described for all new roads.

19 (AB) Where cutbank stability is not an issue, logging roads  
20 ~~may~~ be constructed as a full-benched cut (no fill). Spoils not  
21 utilized in logging road construction shall be disposed of in stable  
22 areas with less than 30 percent slope outside of any WLPZ, EEZ, or ELZ  
23 designated for watercourse or lake protection. The Director, with  
24 concurrence from other responsible agencies, may waive inclusion of  
25 these measures where the RPF can show that slope depressions and other

1 natural retention and detentions feature are sufficient to controls  
2 overland transport of eroded material.

3 (BC) Logging roads may be constructed with balanced cuts  
4 and fills:

5 (i) If properly engineered, or,

6 (ii) If fills are removed and the slopes recontoured  
7 prior to the winter period.

8 (2) October 15 to May 1 shall be considered the extended wet  
9 weather period and the following shall apply:

10 (A) No timber operations shall take place unless the  
11 approved plan incorporates a complete winter period operating  
12 plan pursuant to 14 CCR § 914.7 [934.7, 954.7] subsection (a)  
13 that specifically addresses, where applicable, proposed logging  
14 road- or landing- construction, reconstruction during the  
15 extended wet weather period. ~~From October 15 to May 1, no~~  
16 ~~construction or reconstruction of logging roads or landings shall take~~  
17 ~~place unless the approved plan incorporates a complete winter period~~  
18 ~~operating plan pursuant to 14 CCR § 914.7(a) [934.7(a), 954.7(a)] that~~  
19 ~~addresses such logging road or landing construction or reconstruction.~~

20 **923.5, 943.5, 963.5 Erosion Control for Logging Roads and Landings**

21 The following erosion control standards shall apply to logging roads  
22 and landings:

Formatted: Highlight

Comment [p42]: Incorporates ASP adopted rule language (916.9(1)(1); excludes "use".

1 (a) All logging road and landing surfaces shall be adequately drained  
2 through the use of surface geometry configurations in combination with  
3 the installation of drainage facilities or ditch drains.

4 (b) Drainage facilities or ditch drains shall be installed along all  
5 logging roads and all landings that are used for timber operations in  
6 sufficient number to minimize soil erosion and sediment transport and  
7 to prevent the discharge of sediment into watercourses and lakes in  
8 quantities deleterious to the beneficial uses of water.

9 (c) Ditch drains, associated necessary protective structures, and  
10 other features associated with the ditch drain shall:

11 (1) Be adequately sized to transmit runoff.

12 (2) Minimize erosion of logging road and landing surfaces.

13 (3) Avoid discharge onto fill.

14 (4) Minimize potential adverse impacts to slope stability.

15 (d) Waterbreaks and rolling dips installed across logging roads and  
16 landings shall be located to avoid collecting and discharging  
17 concentrated runoff onto fills, erodible soils, unstable areas, and  
18 connected headwall swales.

19 (e) Where logging roads or landings do not have permanent and  
20 adequate drainage, and where waterbreaks are to be used to control  
21 surface runoff, the waterbreaks shall be cut diagonally a minimum of  
22 six inches into the firm roadbed and shall have a continuous firm  
23 embankment of at least six inches in height immediately adjacent to  
24 the lower edge of the waterbreak cut. On logging roads that have  
25 firmly compacted surfaces, waterbreaks may be installed by hand  
methods and need not provide the additional six-inch embankment

Formatted: Highlight

1 provided the waterbreak ditch is constructed so that it is at least  
2 six inches deep and six inches wide on the bottom and provided there  
3 is ample evidence based on slope, material, amount of rainfall, and  
4 period of use that the waterbreaks so constructed 333 be effective in  
5 diverting water flow from the logging road surface without the  
6 embankment.

Formatted: Highlight

7 **(f) Option 1:** Distances between waterbreaks shall not exceed the  
8 standards specified in 14 CCR § 914.6(c) [(934.6(c), 954.6(c)].

9 **Option 2:** Distances between waterbreaks shall not exceed the  
10 following standards:

11  
12 **MAXIMUM DISTANCE BETWEEN WATERBREAKS**

Estimated Hazard Rating	Logging Road Gradient in Percent		
	10 or less	11-25	>25
	Feet	Feet	Feet
Extreme	100	75	50
High	150	100	75
Moderate	200	150	100
Low	300	200	150

20 **(g)** Where outsloping and rolling dips are used to control surface  
21 runoff, the dip in the logging road grade shall be sufficient to  
22 capture runoff from the logging road surface. The steepness of cross-  
23 slope gradient in conjunction with the logging road or landing  
24 gradient and the estimated soil erosion hazard rating shall be used to  
25 determine the rolling dip spacing in order to minimize soil erosion

1 and sediment transport and to prevent the discharge of sediment into  
2 watercourses and lakes in **quantities deleterious** to the beneficial  
3 uses of water.

Formatted: Highlight

4 **(h)** Drainage facilities and ditch drains shall discharge into  
5 vegetation or rock wherever possible. Where erosion-resistant  
6 material is not present, slash, rock, or other energy dissipating  
7 material shall be installed below the drainage facility or drainage  
8 structure outlet.

9 **(i)** All logging roads and landings used for timber operations shall  
10 have adequate drainage upon completion of use for the year or by  
11 October 15 whichever is earlier. An exception is that drainage  
12 facilities and drainage structures do not need to be constructed on  
13 logging roads in use after October 15 provided that all such drainage  
14 facilities and drainage structures are installed prior to the start of  
15 rain that generates overland flow.

16 **(j)** Where logging road or landing construction or reconstruction  
17 takes place from October 15 to May 1, drainage facilities and drainage  
18 structures shall be installed concurrent with construction or  
19 reconstruction operations.

20 **(k)** Bare soil on logging road or landing cuts, fills, transported  
21 spoils, or sidecast that is created or exposed by timber operations  
22 shall be stabilized to the extent necessary to minimize soil erosion  
23 and sediment transport and to prevent the discharge of sediment into  
24 watercourses and lakes in **quantities deleterious** to the beneficial  
25 uses of water. Sites to be stabilized include, but are not limited  
to:

Formatted: Highlight

1 (1) Sidecast or fill exceeding 20 feet in slope distance from  
2 the outside edge of a logging road or a landing that has access to a  
3 watercourse or lake.

4 (2) Approaches to logging road watercourse crossings of Class I  
5 or II waters or Class III waters where an ELZ, EEZ, or a WLPZ is  
6 required.

7 (3) Bare areas exceeding 800 continuous square feet within a  
8 WLPZ.

9 (1) Soil stabilization measures shall be described in the plan and  
10 include, but are not limited to, removal, armoring with rip-rap,  
11 replanting, mulching, seeding, installing commercial erosion control  
12 devices to manufacturer's specifications, or chemical stabilizers.

13 (m) Where the natural ability of ground cover within a WLPZ is  
14 inadequate to protect the beneficial uses of water by minimizing soil  
15 erosion or by filtering sediments, the plan shall specify protection  
16 measures to retain and improve the natural ability of the ground cover  
17 to filter sediment and minimize soil erosion.

18 (n) Soil stabilization treatments shall be in place upon completion  
19 of operations for the year of use or prior to October 15, whichever  
20 comes first. An exception is that bare areas created on or after  
21 October 15 shall be treated within 10 days or as agreed to by the  
22 Director.

23 (o) Overhanging or unstable concentrations of slash, woody debris or  
24 soil along the downslope edge or face of landings shall be removed or  
25 stabilized when it is located on slopes greater than 65 percent or  
within 100 feet of the boundary of a WLPZ on slopes greater than 50

Formatted: Highlight

Comment [p43]: NOTE: This provision addresses ASP rule 916.9(n)(7) for areas within a WLPZ (old T/I 916.9(n)(4)).

1 percent that drain toward the zoned watercourse or lake. Removed  
2 materials shall not be placed at disposal sites that **could** discharge  
3 into a watercourse or lake in **quantities deleterious** to the beneficial  
4 uses of water.

Formatted: Highlight

Formatted: Highlight

5 **(p)** In watersheds with ~~threatened or impaired values~~ listed anadromous  
6 salmonids, the following shall apply:

7 **(1)** Constructed and reconstructed logging roads shall be  
8 outsloped where feasible and drained with waterbreaks or rolling dips  
9 (where the road grade is inclined at seven (7) percent or less) in  
10 conformance with other applicable Forest Practice Rules.

11 **(2)** In addition to the provisions listed under 14 CCR §  
12 923.2(ed) (52) [943.2(ed) (52), 963.2(ed) (52)], all permanent and  
13 seasonal logging roads with a grade of 15 percent or greater that  
14 extend 500 continuous feet or more shall have specific erosion control  
15 measures stated in the plan.

Comment [p44]: Corrected rule references.

16 **(3)** **Within** the WLPZ, and within any ELZ or EEZ designated for  
17 watercourse or lake protection, treatments to stabilize soils,  
18 minimize soil erosion, and prevent the discharge of sediment into  
19 watercourses or lakes in **quantities deleterious** to aquatic species or  
20 the quality and beneficial uses of water, or that threaten to violate  
21 applicable water quality requirements shall be described in the plan  
22 as follows:

Comment [p45]: Revised to be consistent with the ASP rule 916.9(n).

Comment [p46]: RRTF uses the term "quantities" throughout the package; ASP rule 916.9(n) uses "amounts" Other recently adopted ASP rules use one or the other.

Formatted: Highlight

Formatted: Highlight

23 **(A)** In addition to the requirements of subsections (~~l~~k)-  
24 (~~o~~o), soil stabilization is required for the following areas:

Comment [p47]: Corrected subsection references.

Comment [p48]: ASP requirement 916.9(n)(1)(B) has been deleted as it addresses tractor roads.

1 (i) Areas exceeding 100 continuous square feet where  
2 timber operations have exposed ~~more than 100 continuous square feet of~~  
3 bare soil.

4 (ii) ~~Disturbed r~~oad cut banks and fills, ~~and-~~

5 (iii) Any other area of disturbed soil that threatens  
6 to discharge sediment into water in quantities deleterious to the  
7 quality and beneficial uses of water.

8 (B) Where straw mulch is used, the minimum straw coverage  
9 shall be 90 percent, and any treated area that has been reused or has  
10 less than 90 percent surface cover shall be treated again by the end  
11 of timber operations.

12 (C) Where slash mulch is packed into the ground surface  
13 through the use of a tractor or equivalent piece of heavy equipment  
14 used, the minimum slash coverage shall be 90 percent, or 75 percent  
15 where the slash is packed into the ground surface through the use of a  
16 tractor or equivalent piece of heavy equipment.

17 (D) For areas disturbed from May 1 to October 15,  
18 ~~treatment~~s shall be completed prior to the start of any rain that  
19 causes overland flow across or along the disturbed surface that soils  
20 deliver sediment into a watercourse or lake in quantities deleterious  
21 to the beneficial uses of water.

22 (E) For areas disturbed from October 15 to May 1,  
23 treatment shall be completed prior to any day for which a chance of  
24 rain of 30 percent or greater is forecast by the National Weather  
25 Service or within 10 days of disturbance, whichever is earlier.

Comment [p49]: ASP rule changes.

Comment [p50]: ASP rule changes.

Comment [p51]: NOTE: ASP requirement 916.9(n)(2) is addressed in statewide subsection 923.5(1) above.

Formatted: Highlight

Formatted: Highlight

1 (F) Where the natural ability of ground cover within  
2 within any ELZ or EEZ designated for watercourse or lake protection is  
3 inadequate to protect the beneficial uses of water by minimizing soil  
4 erosion or by filtering sediments, the plan shall specify protection  
5 measures to retain and improve the natural ability of the ground cover  
6 to filter sediment and minimize soil erosion.

**Comment [p52]:** NOTE: This provision from ASP rule 916.9(n)(7) covers ELZ and EEZ areas not covered under statewide subsection(m).

7  
8 **923.6, 943.6, 963.6 Use for Logging Roads and Landings**

9  
10 The following use standards shall apply to logging roads and landings:

11 (a) Logging roads and landings shall be used in a manner that is  
12 consistent with their design and construction specifications.

13 (b) Logging roads and landings shall not be used when conditions that  
14 could result in sediment discharge into watercourses or lakes in  
15 quantities deleterious to the beneficial uses of water, except in  
16 emergencies to protect the road, to reduce erosion, to protect water  
17 quality, or in response to public safety needs.

**Formatted: Highlight**

18 (c) Logging roads and landings shall not be used when, due to general  
19 wet conditions, equipment cannot operate under its own power. Use  
20 occur when logging roads and landings are generally firm and easily  
21 passable or during hard frozen conditions. Isolated wet spots on  
22 these logging roads or landings shall be rocked or otherwise treated  
23 to permit passage.

**Formatted: Highlight**

24 (d) When burning permits are required pursuant to PRC § 4423, logging  
25 roads and landings that are in use shall be kept in passable condition  
for fire trucks.

1 (e) All roadside berms shall be removed or breached before the  
2 beginning of the winter period, with the exception of berms needed for  
3 erosion control.

4 (f) ~~Abandoned~~ and deactivated logging roads shall be blocked or  
5 otherwise closed before the winter period to prevent use by normal  
6 vehicular traffic. OR Temporary roads shall be blocked or otherwise  
7 closed to normal vehicular traffic before the winter period.

8 (g) Logging roads and landings shall not be used for log hauling  
9 between October 15 and May 1 when saturated soil conditions ~~exist on~~  
10 the logging road or landing ~~do not minimize soil erosion and sediment~~  
11 ~~transport and prevent the discharge of sediment into watercourses and~~  
12 ~~lakes in quantities deleterious to the beneficial uses of water.~~

13 (h) Logging roads and landings used for log hauling during the winter  
14 period shall be, where necessary, surfaced with rock to a depth and  
15 quantity sufficient to maintain a stable road surface throughout the  
16 period of use.

17 (i) In watersheds with ~~listed anadromous salmonids threatened or~~  
18 ~~impaired values~~, the following shall apply:

19 (1) Existing logging roads or landings shall not be used within  
20 the channel migration zone of a Class I watercourse except as listed in  
21 14 CCR § 916.9 [936.9,956.9], subsection (e)(1)(A)-(F) or pursuant to 14 CCR §  
22 916.9 [936.9, 956.9], subsection (v)..

23 (2) When feasible, minimize use of existing logging roads and  
24 landings located within Inner Zones A and B of flood prone areas.

**Comment [p53]:** Existing 923.4(b) requires temporary roads/landing be abandoned per existing 923.8 (blockage to standard production four wheel drive highway vehicles). Existing 923.4(g) requires blockage to prevent use by normal vehicular traffic. Thus, existing rules are not consistent with regards to blockage. The proposed rule eliminates reference to temporary roads and replaces them with abandoned and deactivated roads which already have a blockage requirement under subsection 923.8(f). **Suggest retaining current rule (g) to address temporary roads and distinguishing them from deactivated or abandoned roads or require the same blockage standard.** See RRTF revised definition of temporary road. Revision is needed to eliminate conflict between the two rule subsections (normal vehicular traffic versus standard production four wheel drive highway vehicles). If rule reverts back to temporary roads may want to consider adding timing of blockage to proposed 923.8(f).

**Comment [p54]:** . NOTE: due to the change in the ASP definition of saturated soil conditions the original RRTF rule subsection (existing 923.1(j)) should be revised to re-establish the linkage between the road conditions and minimizing/preventing negative WQ impacts by modifying the end of the subsection in a manner consistent with other rules.

**Comment [p55]:** Consistent with planning requirement 923.1(g) and construction requirement 923.4(r)-Option 2. Use could either be facilitated by a channel zone exception or a site specific measure or nonstandard operational provision pursuant to 916.9(v).

1 (A) Exceptions include the use of roads and landings to  
2 accomplish actions to improve salmonid habitat conditions stated in 14  
3 CCR § 916.9 [936.9, 956.9]. subsection (f) (3) (E) (1.)

4 (13) Logging roads and landings shall not be used when visibly  
5 turbid water from the road or landing surface or an inside ditch  
6 associated with the logging road or landing ~~can~~ reach a watercourse or  
7 lake in amounts sufficient to cause a turbidity increase in Class I,  
8 II, III or IV waters.

Formatted: Highlight

Comment [p56]: Modified to be consistent with ASP rule 916.9(k) (1).

9 (24) Log hauling on logging roads and landings shall be limited  
10 to those which are hydrologically disconnected from watercourses to  
11 the extent feasible, and exhibit a stable operating surface in  
12 conformance with (1) above. ~~The operation of trucks and heavy equipment~~  
13 ~~on logging roads and landings shall be limited to those with a stable~~  
14 ~~operating surface where saturated soil conditions are not present.~~

Comment [p57]: Modified to incorporate ASP rule 916.9(k) (2). NOTE: This subsection may be redundant to other performance based requirements in the RRTF package.

15 (35) Concurrent with use for log hauling, approaches to logging  
16 road watercourse crossings shall be treated for erosion control as  
17 needed to minimize soil erosion and sediment transport and to prevent  
18 the discharge of sediment into watercourses and lakes in ~~quantities~~  
19 ~~deleterious~~ to the beneficial uses of water.

Formatted: Highlight

Comment [p58]: Incorporates ASP rule 916.9(k) (3)

20 (46) Concurrent with use for log hauling, all traveled surfaces  
21 of logging roads in a WLPZ or within any ELZ or EEZ designated for  
22 watercourse or lake protection shall be treated for erosion control as  
23 needed to minimize soil erosion and sediment transport and to prevent  
24 the discharge of sediment into watercourses and lakes in ~~quantities~~  
25 ~~deleterious~~ to the beneficial uses of water.

Formatted: Highlight

Comment [p59]: Incorporates ASP rule 916.9(k) (4).

1 ~~(5) Prior to use, approaches to water drafting locations within~~  
2 ~~a WLPZ shall be surfaced with rock or other suitable material to avoid~~  
3 ~~generation of sediment.~~

**Comment [p60]:** This water drafting requirement is specified under 923.7(1)(2).

4 ~~(67)~~ **October** 15 to May 1 shall be considered the extended wet weather  
5 period and the following shall apply:

Note: ASP rule 916.9(k)(5) addressing road grading is located under Maintenance and Monitoring

6 **(A)** No timber operations shall take place unless the approved plan  
7 incorporates a complete winter period operating plan pursuant to 14 CCR §  
8 914.7 [934.7, 954.7] subsection (a) that specifically addresses, where  
9 applicable, proposed logging road= or landing= use during the extended wet  
10 weather period. ~~From October 15 to May 1 logging roads and landings~~  
11 ~~shall not be used unless the approved plan incorporates a complete~~  
12 ~~winter period operating plan pursuant to 14 CCR § 914.7(a) [934.7(a),~~  
13 ~~954.7(a)] that addresses such logging road and landing use.~~

**Comment [p61]:** Incorporates ASP adopted rule language (916.9(1)(1); regarding "use".

14 **(B)** Logging roads and landings shall not be used when sediment  
15 from the logging road or landing road surface is transported to a  
16 watercourse or a drainage facility that discharges into a watercourse  
17 in amounts sufficient to cause a visible increase in turbidity in  
18 Class I, II, III, or IV **waters**.

**Comment [p62]:** Modified to incorporate ASP rule 916.9(1)(3); excludes references to tractor roads.

19 **(C)** Logging roads and landings shall not be used for log  
20 hauling when saturated soil conditions result in the visible increase  
21 in turbidity specified in (B) **above**.

**Comment [p63]:** Modified to incorporate ASP rule 916.9(1)(4). Replaces previous proposed RRTF subsection (i)(2).

24 **923.7, 943.7, 963.7 Maintenance and Monitoring for Logging Roads and**  
25 **Landings**

1 The following maintenance and monitoring standards shall apply to  
2 logging roads and landings:

3 (a) Logging road and landing surfaces shall be maintained during  
4 timber operations and throughout the prescribed maintenance period to  
5 minimize soil erosion and sediment transport and to prevent the  
6 discharge of sediment into watercourses and lakes in **quantities**  
7 **relatively** to the beneficial uses of water.

Formatted: Highlight

8 (b) Logging roads that are used in connection with stocking  
9 activities shall be maintained throughout such use, even if this  
10 extends beyond the prescribed maintenance period.

11 (c) Maintenance treatments to the running surfaces of logging roads  
12 and landing surfaces shall be described in the plan and **may** include,  
13 but not be limited to, rocking, watering, paving, chemically treating,  
14 or installing commercial erosion control devices to manufacturer's  
15 specifications.

Formatted: Highlight

16 (d) Drainage facilities and drainage structures, including associated  
17 necessary protective structures, shall be maintained to allow free  
18 flow of water and minimize soil erosion or they shall be repaired,  
19 replaced, or installed when maintenance is needed to protect the  
20 quality and beneficial uses of water.

21 (e) Waterbreaks shall be maintained as specified in 14 CCR § 914.6(h)  
22 [934.6(h), 954.6(h)].

23 (f) Soil stabilization treatments on logging road or landing cuts,  
24 fills, and sidecast shall be maintained as needed to minimize soil  
25 erosion and sediment transport and to prevent sediment discharge into

1 watercourses and lakes in ~~quantities deleterious~~ to the beneficial  
2 uses of water.

Formatted: Highlight

3 (g) Actions shall be taken as needed to reduce the potential for  
4 failures of cuts, fills, or sidecast to discharge sediment into  
5 watercourses and lakes in ~~quantities deleterious~~ to the beneficial  
6 uses of water.

Formatted: Highlight

7 (h) Heavy equipment shall not be used in a WLPZ for maintenance  
8 during wet weather, except in emergencies to protect the road, to  
9 reduce erosion, to protect water quality, or in response to public  
10 safety needs.

11 (i) Where evidence of substantial soil erosion and discharge of  
12 sediment into watercourses or lakes in ~~quantities deleterious~~ to the  
13 beneficial uses of water is present along a logging road or landing  
14 used for timber operations, additional drainage facilities and  
15 structures shall be installed as needed to minimize soil erosion and  
16 sediment transport and to prevent the discharge of sediment into  
17 watercourses and lakes in ~~quantities deleterious~~ to the beneficial  
18 uses of water.

Formatted: Highlight

19 (j) The prescribed maintenance period for erosion controls on  
20 permanent and seasonal logging roads and associated landings and  
21 drainage structures, which are not abandoned or deactivated in  
22 accordance with 14 CCR §§ 923.8 [943.8, 963.8] and 923.17 [943.17,  
23 963.17], shall be at least one year. The Director ~~may~~ prescribe a  
24 maintenance period extending up to three years in accordance with 14  
25 CCR § 1050.

Formatted: Highlight

Formatted: Highlight

1 (k) Logging roads, landings, and associated drainage structures used  
2 for timber operations shall be monitored as needed to comply with 14  
3 CCR § 1050.

4 (1) In watersheds with ~~threatened or impaired values~~ listed anadromous  
5 salmonids, the following shall apply:

6 (1) Grading logging roads or landings to obtain a drier running  
7 surface more than one time before reincorporation of any resulting  
8 berms back into the road surface is prohibited.

9 (2) Water drafting for timber operations shall:

10 (A) Comply with Fish and Game Code Section 1600, et seq.

11 1. Timber operations conducted under a Fish and Game Code Section  
12 1600 master or long-term agreement that includes water drafting may provide proof of such  
13 coverage for compliance with this paragraph.

14 (B) Describe the water drafting site conditions and proposed water drafting activity in the  
15 plan, including:

- 16 1. a general description of the conditions and proposed water drafting;
- 17 2. a map showing proposed water drafting locations;
- 18 3. the watercourse classification;
- 19 4. the drafting parameters including the months the site is proposed for  
20 use; estimated total volume needed per day; estimated maximum instantaneous drafting rate  
21 and filling time; and disclosure of other water drafting activities in the same watershed;
- 22 5. the estimated drainage area (acres) above the point of diversion;
- 23 6. the estimated unimpeded streamflow, pumping rate, and drafting  
24 duration,
- 25 7. a discussion of the effects on aquatic habitat downstream from the

**Comment [p64]:** Incorporates a slightly different version (non-substantive) of ASP rule subsection 916.9(k) (5)

**Comment [p65]:** ASP rule 916,9(r) for water drafting incorporated here.

1 drafting site(s) of single pumping operations, or multiple pumping operations at the same  
2 location, and at other locations in the same watershed;

3                   8. a discussion of proposed alternatives and measures to prevent  
4 adverse effects to fish and wildlife resources, such as reducing hose diameter; using gravity-fed  
5 tanks instead of truck pumping; reducing the instantaneous or daily intake at one location;  
6 describing allowances for recharge time; using other dust palliatives; and drafting water at  
7 alternative sites; and

8                   9. The methods that will be used to measure source streamflow prior to  
9 the water drafting operation and the conditions that will trigger streamflow to be measured  
10 during the operation.

11                   (C) All water drafting for timber operations are subject to each requirement  
12 below unless the Department of Fish and Game modifies the requirement in the Lake or  
13 Streambed Alteration agreement that authorized the drafting operation, or unless otherwise  
14 specified below:

15                   1. All intakes shall be screened to prevent impingement of juvenile fish  
16 against the screen. The following requirements apply to screens and water drafting on Class I  
17 waters:

18                   i. Openings in perforated plate or woven wire mesh screens shall  
19 not exceed 3/32 inches (2.38 millimeters). Slot openings in wedge wire screens shall not  
20 exceed 1/16 inches (1.75 millimeters).

21                   ii. The screen surface shall have at least 2.5 square feet of  
22 openings submerged in water.

23                   iii. The drafting operator shall regularly inspect, clean, and  
24 maintain screens to ensure proper operation whenever water is drafted.

25                   iv. The approach velocity (water moving through the screen) shall  
not exceed 0.33 feet/second.

1 v. The diversion rate shall not exceed 350 gallons per minute.

2 2. Approaches and associated drainage features to drafting locations  
3 within a WLPZ or channel zone shall be surfaced with rock or other suitable material to minimize  
4 generation of sediment.

5 3. Barriers to sediment transport, such as straw waddles, logs, straw  
6 bales or sediment fences, shall be installed outside the normal high water mark to prevent  
7 sediment delivery to the watercourse and limit truck encroachment.

8 4. Water drafting trucks parked on streambeds and floodplains shall use  
9 drip pans or other devices such as absorbent blankets, sheet barriers or other materials as  
10 needed to prevent soil and water contamination from motor oil or hydraulic fluid leaks.

11 5. Bypass flows for Class I watercourses shall be provided in volume  
12 sufficient to avoid dewatering the watercourse and maintain aquatic life downstream, and shall  
13 conform to the following standard:

14 i. Bypass flows in the source stream during drafting shall  
15 be at least 2 cubic feet per second.

16 ii. Diversion rate shall not exceed 10 percent of the surface flow.

17 iii. Pool volume reduction shall not exceed 10 percent.

18 6. The drafting operator shall keep a log that records for each time water  
19 is drafted, the date, total pumping time, pump rate, starting time, ending time, and volume  
20 diverted. Logs shall be filed with the Department of Forestry and Fire Protection at the end of  
21 seasonal operations and maintained with the plan record. This requirement may be modified in  
22 the approved plan that covers the water drafting, but only with concurrence from the Department  
23 of Fish and Game.

24 7. Before commencing any water drafting operation, the RPF and the  
25 drafting operator shall conduct a pre-operations field review to discuss the water drafting  
measures in the plan and/or Lake or Streambed Alteration Agreement.

1  
2 ~~(33)~~ The erosion control maintenance period on permanent and  
3 seasonal logging roads and associated landings that are not abandoned  
4 or deactivated in accordance with 14 CCR § 923.8 [943.8, 963.8] shall  
5 be three years.

**Comment [p66]:** Incorporates ASP subsection 916.9(p) that was removed from that set of rules.

6  
7 **923.8, 943.8, 963.8 Abandonment and Deactivation of Logging Roads and**  
8 **Landings**

9  
10 All logging roads and landings that are proposed to be removed from  
11 the permanent road network, including historic roads and landings,  
12 shall be abandoned. All temporary logging roads and landings that are  
13 to remain a part of the permanent road network shall be deactivated  
14 upon completion of timber operations. Other logging roads and  
15 landings proposed to be deactivated shall comply with the standards  
16 specified in this section. Where abandonment or deactivation is  
17 required or proposed, specific measures used to apply the following  
18 general requirements shall be described in the plan:

- 19 **(a)** All abandoned and deactivated logging roads shall be left in a  
20 condition that provides for long-term functioning of erosion controls.  
21 **(b)** Soil exposed by abandonment or deactivation operations on cuts,  
22 fills, and sidecast shall be stabilized as needed during and upon  
23 completion of abandonment or deactivation operations to minimize soil  
24 erosion and sediment transport and to prevent the discharge of  
25 sediment into watercourses and lakes in quantities deleterious to the  
beneficial uses of water.

**Formatted:** Highlight

1 (c) Logging road and landing surfaces shall be graded or shaped where  
2 needed to disperse runoff.

3 (d) Fills or sidecast shall be pulled or shaped where site conditions  
4 indicate that there is a reasonable potential for perched materials to  
5 enter a watercourse or lake in quantities deleterious to the  
6 beneficial uses of water.

Formatted: Highlight

7 (e) Logging road watercourse crossings, other drainage structures,  
8 and associated fills shall be removed and stabilized in accordance  
9 with 14 CCR § 923.17(a)-(c) [943.17(a)-(c), 963.17(a)-(c)]. Where it  
10 is not feasible to remove drainage structures and associated fills,  
11 the plan shall identify how the potential for soil erosion and  
12 sediment transport will be minimized and how the discharge of sediment  
13 into watercourses and lakes in quantities deleterious to the  
14 beneficial uses of water will be prevented.

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

15 (f) Logging roads to be abandoned or deactivated shall be blocked so  
16 that standard production four wheel-drive highway vehicles cannot pass  
17 the point of closure at the time of abandonment or deactivation. If  
18 the logging road is to be abandoned, then the blockage design shall be  
19 described in the plan.

21 **923.9, 943.9, 963.9 Licensed Timber Operator Responsibility for**  
22 **Logging Roads and Landings**

23  
24 The licensed timber operator who is responsible for the implementation  
25 or execution of the plan shall be responsible for the construction and  
maintenance of logging roads and landings, unless another licensed

1 timber operator is employed for that purpose and amended into the plan  
2 as the responsible party.

3  
4 **923.10, 943.10, 963.10 Planning for Logging Road Watercourse Crossings**

5  
6 The following planning standards shall apply to logging road  
7 watercourse crossings:

8 (a) Logging road watercourse crossings shall be planned and located  
9 within the context of a systematic logging road layout pattern.

10 (b) Logging road watercourse crossings shall be planned in a manner  
11 that is consistent with their proposed use.

12 (c) The number of logging road watercourse crossings shall be kept to  
13 a feasible minimum.

14 (d) Existing logging road watercourse crossing locations shall be  
15 utilized where feasible and appropriate.

16 (e) Where logging road watercourse crossings are proposed to be  
17 constructed or reconstructed in areas where public safety (b) be  
18 affected, the potential public safety impacts shall be disclosed in  
19 the plan.

Formatted: Highlight

20 (f) As part of the field examination of classified watercourses and  
21 lakes, the RPF or supervised designee shall evaluate areas at and near  
22 existing and constructed or reconstructed logging road watercourse  
23 crossings for sensitive conditions, including, but not limited to,  
24 past diversion, overtopping, plugging, significant inlet or outlet  
25 erosion, and significant mechanical damage or wear.

1 (1) The RPF shall consider these conditions, and those measures  
2 needed to maintain, and restore to the extent feasible, the functions  
3 set forth in 14 CCR § 916.4(b) [936.4(b), 956.4(b)], when planning  
4 logging road watercourse crossings.

5 (2) The plan shall identify such conditions, including where  
6 they ~~may~~ interact with proposed timber operations, that individually  
7 or cumulatively, significantly and adversely affect the beneficial  
8 uses of water.

Formatted: Highlight

9 (3) The RPF shall describe in the plan feasible protection  
10 measures for identified sensitive conditions that consider the  
11 watercourse classification and the location and planned use of logging  
12 roads and landings.

13 (4) Where feasible protection measures are proposed, the RPF  
14 shall specify an implementation schedule in the plan.

15 (g) The RPF shall disclose in the plan how diversion of stream  
16 overflow at logging road watercourse crossings ~~may~~ be prevented.

Formatted: Highlight

17 (h) **Option 1:** Where logging road networks are remote or are located  
18 where the landscape is unstable, where crossing fills over culverts  
19 are large, or where logging road watercourse crossing drainage  
20 structures and erosion control features historically have a high  
21 failure rate, drainage structures and erosion control features shall  
22 be oversized, designed for low maintenance, reinforced, or removed  
23 before the completion of the timber operation. **Option 2:** *[Do not*

**Comment [p67]:** Option 1 requires addressing "high-risk" crossings on a statewide basis (as opposed to only in watersheds with listed anadromous salmonids) except for not having to specify the method of analysis and design for crossing protection in the plan.

24 *adopt Option 1 and begin renumbering (h) as (g), (i) as (h), etc.]*

**Comment [p68]:** Option 2 does not make this requirement applicable statewide.

25 (i) All ~~new~~ permanent constructed or reconstructed logging road  
watercourse crossing ~~structures-culverts~~ installed on Class I

**Comment [p69]:** NOTE: subsection lettering from this point on in this Section is subject to whether (h) above is adopted.

1 watercourses, where fish are always or seasonally present or where  
2 fish habitat is restorable, ~~which meet the criteria of Class I waters~~  
3 ~~based on biological characteristics~~, shall be planned to allow  
4 upstream and downstream passage of fish or listed aquatic species  
5 during any life stage and for the natural movement of bedload to form  
6 a continuous bed through the culvert.

**Comment [p70]:** NOTE: other similar worded statewide subsections taken from 923.3(g) are addressed under design and construction to ensure all phases are covered.

**Comment [p71]:** NOTE: the specifications required under subsection 923.3(g) are found under design.

7 (j) In watersheds with ~~threatened or impaired values~~ listed anadromous  
8 salmonids, the following shall apply:

9 (1) ~~For Class I waters, any plan involving timber operations~~  
10 ~~within the WLPZ shall contain the following information:~~

11 ~~(A) A description of all existing permanent logging road~~  
12 ~~watercourse crossings.~~

**Comment [p72]:** Moved from planning to design and implementation 923.11(k).

13 ~~(B) Clear specifications regarding how these crossings are~~  
14 ~~to be modified, used, and treated to achieve the standards of~~  
15 ~~subsection (i).~~

**Comment [p73]:** Moved from planning to design and implementation 923.11(k).

16 ~~(C) Clear and enforceable specifications for construction~~  
17 ~~and operation of any new crossing to prevent direct harm, habitat~~  
18 ~~degradation, water velocity increase, hindrance of fish passage, or~~  
19 ~~other potential impairment of the beneficial uses of water.~~

**Comment [p74]:** Moved from planning to construction 923.13(k).

20 (2) ~~Option 1:~~ Where logging road networks are remote or are  
21 located where the landscape is unstable, where crossing fills over  
22 culverts are large, or where logging road watercourse crossing  
23 drainage structures and erosion control features historically have a  
24 high failure rate, drainage structures and erosion control features  
25 shall be oversized, designed for low maintenance, reinforced, or  
removed before the completion of the timber operation. The method of

**Comment [p75]:** This requirement is not an option in watersheds with listed anadromous salmonids (see 923.9(e)).

1 analysis and the design for crossing protection shall be included in  
2 the plan.

3 ~~Option 2 [This only applies if subsection (h), Option 1 is adopted]:~~

4 In addition to the requirements of 923.10(h), the method of analysis  
5 and the design for crossing protection shall be included in the plan.

6 ~~Option 3: [This only applies if subsection (h), Option 1 is adopted]:~~

7 ~~Do not adopt Option 1 or Option 2.~~

**Comment [p76]:** If subsection(h) is adopted statewide then adopting Option 2 would make the combination of both equivalent to a stand-alone Option 1 above for watersheds with listed anadromous salmonids.

**Comment [p77]:** Option 3 has been deleted as a stand-alone (h) is not in conformance for watersheds with listed anadromous salmonids.

8  
9 **923.11, 943.11, 953.11 Logging Road Watercourse Crossing Design and**  
10 **Implementation**

11  
12 The following design and implementation standards shall apply to  
13 logging road watercourse crossings:

14 **(a)** All constructed and reconstructed logging road watercourse  
15 crossings shall be designed in accordance with the planned use of the  
16 associated logging road.

17 **(b)** All logging road watercourse crossings shall be designed to avoid  
18 or mitigate potential significant adverse impacts to public safety.

19 **(c)** All constructed and reconstructed permanent logging road  
20 watercourse crossing structures shall be designed to accommodate the  
21 estimated 100-year flood flow, including debris and sediment loads.

22 ~~Exceptions may be explained and justified in the plan and approved by~~  
23 ~~the Director where existing crossings located in the same~~  
24 ~~physiographic environment have remained intact and undamaged following~~  
25 ~~stressing storms.~~

**Formatted:** Highlight

**Comment [p78]:** NOTE: concept was rejected as a categorical exception under the ASP rules and therefore has been deleted.

1 (d) All new and replacement culverts used for logging road  
2 watercourse crossings shall be designed to be installed at or slightly  
3 below the natural watercourse grade.

4 (e) Where new culverts are proposed for permanent installation at a  
5 logging road watercourse crossing, the minimum diameter of the culvert  
6 and the method used to determine the culvert diameter shall be  
7 specified in the plan.

8 (f) All necessary protective structures associated with logging road  
9 watercourse crossings shall be adequately sized to transmit runoff,  
10 minimize erosion of crossing fills, and prevent the discharge of  
11 sediment into watercourses and lakes in **quantities deleterious** to the  
12 beneficial uses of water.

Formatted: Highlight

13 (g) Methods to mitigate or prevent diversion of stream overflow at  
14 logging road watercourse crossings shall be stated in the plan.

15 (h) Rock used to stabilize the outlet of fords shall be adequately  
16 sized to resist mobilization, with the range of required rock  
17 dimensions described in the plan.

18 (i) Drainage structures on watercourses that support fish shall allow  
19 for unrestricted passage of all life stages of fish that may be  
20 present, and shall be fully described in the plan in sufficient  
21 clarity and detail to allow evaluation by the review team and the  
22 public, provide direction to the LTO for implementation, and provide  
23 enforceable standards for the **inspector**.

Comment [p79]: NOTE: new RIBAR addition to the RRTF package. This requirement has been added for conformance with 923.3(c).

24 (~~j~~) All **new** permanent constructed and reconstructed logging road  
25 watercourse crossing ~~structures-culverts~~ installed within Class I  
watercourses, which meet the criteria for Class I waters **where fish**

1 are always or seasonally present or where fish habitat is  
2 restorable based upon biological characteristics, shall include the  
3 analysis and specifications that document conformance with 14 CCR §  
4 923.10(i) [943.10(i), 963.10(i)].

5 ~~(jk)~~ In watersheds with ~~threatened or impaired values~~ anadromous  
6 salmonids, ~~for~~ Class I watercourses, where fish are always or  
7 seasonally present or where fish habitat is restorable, any plan  
8 involving timber operations within the WLPZ shall contain the  
9 following information:

10 (1) A description of all existing permanent logging road  
11 watercourse crossings.

12 (2) Clear and enforceable specifications describing how  
13 these crossings are to be modified, used, and treated to minimize  
14 risks, giving special attention to allowing fish to pass both upstream  
15 and downstream during all life stages and in conformance with the  
16 standards of subsection (j) above and 14 CCR § 923.10(i) [943.10(i),  
17 963.10(i)].

18 ~~the RPF shall state in the plan how existing permanent~~  
19 ~~culverts used for logging road watercourse crossings on Class I~~  
20 ~~watercourses, which meet the criteria for Class I waters based upon~~  
21 ~~biological characteristics, shall be brought up to the standards of~~  
22 ~~subsection (i) above and 14 CCR § 923.10(i) [943.10(i), 963.10(i)].~~

23  
24 923.12, 943.12, 963.12 Logging Road Watercourse Crossing Mapping and  
25 Identification

**Comment [p80]:** Addresses 923.3(g) statewide design requirements for new CI logging road watercourse crossings (from 923.3(g)); broadened from culverts to drainage structures. NOTE: other similar worded subsections taken from 923.3(g) are addressed under planning and construction to ensure all phases are covered.

**Comment [p81]:** ASP requirements 916.9(f)(1)(B) and (C). Note: these two requirements are largely redundant to statewide requirement (i) above.

**Comment [p82]:** Combines ASP requirement 916.9(f)(1)(C) and previous RRIF subsection (i).

**Comment [p83]:** Moved to subsection (j) above as this requirement is applicable statewide not just in watersheds with listed anadromous salmonids;.

1 The following mapping and identification standards shall apply to  
2 logging road watercourse crossings:  
3 (a) For logging road watercourse crossing-related mapping  
4 requirements refer to 14 CCR §§ 1034(x)(6)(A)-(C), 1090.5(w)(7),  
5 1090.7(n)(7), and 1092.09(1)(7)(A)-(C).  
6 (b) For logging road watercourse crossing-related disclosure and  
7 description requirements refer to 14 CCR §§ 1034(ii)(18) and 1034(11).  
8 (c) The location of all logging road watercourse crossings to be  
9 constructed or reconstructed shall be flagged or otherwise identified  
10 on the ground before **Option 1:** before submission of a plan or  
11 substantial deviation (**Option 2:** prior to the pre-harvest inspection,  
12 if necessary, or prior to logging road watercourse crossing  
13 construction or reconstruction). Exceptions **can** be explained and  
14 justified in the plan and agreed to by the Director if flagging is  
15 unnecessary as a substantial aid to examining possible significant  
16 adverse effects of the crossing location on the factors listed under  
17 14 CCR § 923(b) [943(b), 963(b)].

Formatted: Highlight

923.13, 943.13, 963.13 Logging Road Watercourse Crossing Construction and Reconstruction

The following construction and reconstruction standards shall apply to logging road watercourse crossings:

(a) Where applicable, logging road watercourse crossing construction and reconstruction shall comply with the design of required DF&G 1600 agreements.

(b) All constructed and reconstructed permanent logging road watercourse crossings shall accommodate the 100-year flood flow, including debris and sediment loads. ~~Exceptions may be explained and justified in the plan and approved by the Director where existing crossings, located in the same physiographic environment, have remained intact and undamaged following stressing storms.~~

Formatted: Highlight

Comment [p84]: NOTE: concept was rejected as a categorical exception under the ASP rules and therefore has been deleted.

(c) All new and replacement culverts used for logging road watercourse crossings shall be installed at or slightly below the natural watercourse grade. For Class I watercourses, which meet the criteria for Class I waters ~~where fish are always or seasonally present or where fish habitat is restorable~~~~based on biological characteristics~~, new and replacement culverts shall be installed below grade to allow upstream and downstream passage of fish or listed aquatic species during any life stage and natural movement of bedload ~~to form a continuous bed through the culvert~~ and shall be in conformance ~~the design specified in 14 CCR § 923.11 (j)~~

Comment [p85]: NOTE: addresses construction; requirements required under subsection 923.3(g), similar requirements are also found under planning and design.

1 [943.11(j), 963.11(j)] and with required DF&G 1600 agreements specified  
2 in subsection (a) above.

3 (d) Fills for constructed and reconstructed logging road watercourse  
4 crossings shall be thoroughly compacted in approximately one-foot  
5 lifts during installation. The face of crossing fills shall be no  
6 greater than 65 percent (1.5:1, horizontal to vertical).

7 (e) Logging road watercourse crossings shall not discharge water onto  
8 erodible fill or other erodible material without the installation of  
9 energy dissipators and other necessary protective structures.

10 (f) Where water is flowing at the time of logging road watercourse  
11 crossing construction or reconstruction, necessary protective  
12 structures shall be concurrently installed.

13 (g) Where a significant volume of sediment is stored upstream from a  
14 logging road watercourse crossing that is proposed to be  
15 reconstructed, the stored sediment shall be removed or stabilized, to  
16 the extent feasible, as described in the plan and in conformance with  
17 required DF&G 1600 agreements.

18 (h) Critical dips shall be incorporated into the construction or  
19 reconstruction of logging road watercourse crossings utilizing  
20 culverts, except where diversion of overflow is prevented by other  
21 methods stated in the plan.

22 (i) Logging road watercourse crossings with sensitive conditions  
23 identified under 14 CCR § 923.10(f) [943.10(f), 963.10(f)] shall be  
24 upgraded to address these conditions, replaced in accordance with 14  
25 CCR § 923.11 [943.11, 963.11] and this section, or removed in  
accordance with 14 CCR § 923.17 [943.17, 963.17].

1 (j) Logging road watercourse crossings shall not be constructed or  
2 reconstructed under saturated soil conditions or when such activities  
3 could result in the discharge of sediment into watercourses or lakes  
4 in quantities deleterious to the beneficial uses of water.

Formatted: Highlight

5 (k) Where conditions are encountered during logging road watercourse  
6 crossing construction or reconstruction that differ from what was  
7 anticipated during the preparation and review of the plan and that  
8 will result in a significant adverse impact on the environment or to  
9 public safety, the LTO shall notify the RPF or plan submitter of these  
10 unanticipated conditions in accordance with 14 CCR § 1035.3. If  
11 necessary, the responsible RPF or plan submitter shall submit to the  
12 Director a proposed deviation to the plan describing the unanticipated  
13 conditions and proposing appropriate actions.

14 (l) Logging road watercourse crossings shall be installed no later  
15 than October 15, except where logging road construction or  
16 reconstruction takes place from October 15 to November 15 or from  
17 April 1 to May 1 where logging road watercourse crossings shall be  
18 installed concurrent with the activity. Logging road watercourse  
19 crossings shall not be installed during the winter period, except as  
20 specified in an approved winter operating plan per 14 CCR § 914.7(a)  
21 [934.7(a), 954.7(a)].

22 (m) In watersheds with anadromous salmonids, for Class I  
23 watercourses, where fish are always or seasonally present or where  
24 fish habitat is restorable, any plan involving timber operations  
25 within the WLPZ shall contain the following information:

(1) Clear and enforceable specifications for construction and

1 operation of any new crossing(s) of a Class I watercourse to prevent  
2 direct harm, habitat degradation, water velocity increase, hindrance  
3 of fish passage, or other potential impairment of beneficial uses of  
4 water.

5 ~~In watersheds with threatened or impaired values, from October 15 to~~  
6 ~~May 1, logging road watercourse crossings shall not be constructed or~~  
7 ~~reconstructed, except as specified in an approved winter operating~~  
8 ~~plan per 14 CCR § 914.7(a) [934.7(a), 954.7(a)] and in conformance~~  
9 ~~with the implementation schedule required per 14 CCR § 923.10(f)~~  
10 ~~[943.10(f), 963.10(f)].~~

11 (n) In watersheds with listed anadromous salmonids, excavated  
12 material and cut bank resulting from construction and reconstruction  
13 shall be sloped back from the channel to prevent slumping and to  
14 minimize soil erosion and where needed, stabilized per 14 CCR §  
15 923.14(b) [943.14(b), 963.14(b)].

16 (o) In watersheds with listed anadromous salmonids, October 15 to May  
17 1 shall be considered the extended wet weather period and the  
18 following shall apply:

19 (1) No timber operations shall take place unless the  
20 approved plan incorporates a complete winter period operating  
21 plan pursuant to 14 CCR § 914.7 [934.7, 954.7] subsection (a)  
22 that specifically addresses, where applicable, proposed logging  
23 road watercourse construction or reconstruction during the  
24 extended wet weather period. Where logging road watercourse  
25 crossing construction or reconstruction is proposed an  
implementation schedule shall be specified.

**Comment [p86]:** Incorporates ASP subsection 916.9(f)(1)(D). Note: this ASP rule requirement may largely be redundant to statewide rule subsection 923.3(g) that has been addressed in the planning, design and construction sections of this package.

**Comment [p87]:** SPITTLER Option. Oversteepened cutbanks and excavated material can slump and result in soil erosion. Sloping of materials reduces risk of slumping and where needed stabilization materials would be applied.

**Comment [p88]:** Incorporates 916.9(k)(1) addressing logging road watercourse crossings. This wording from Original RRTF subsection 923.13(m) required a implementation schedule)

1 923.14, 943.14, 963.14 Logging Road Watercourse Crossing Erosion

2 Control

3  
4 (a) The following drainage standards shall apply to logging road  
5 watercourse crossings:

6 (1) Adequate surface drainage at logging road watercourse  
7 crossings shall be provided through the use of surface geometry  
8 configurations in combination with the installation of drainage  
9 facilities, ditch drains, or other necessary protective structures.

10 (2) Drainage facilities and ditch drains shall be installed  
11 adjacent to logging road watercourse crossings, as needed, to minimize  
12 soil erosion and sediment transport and to prevent the discharge of  
13 sediment into watercourses and lakes in quantities deleterious to the  
14 beneficial uses of water during and upon completion of timber  
15 operations. See 14 CCR §§ 923.5(d)-(j) for standards related to  
16 waterbreak and rolling dip installation.

17 (3) Drainage facilities or ditch drains installed adjacent to  
18 logging road watercourse crossings shall be located to avoid  
19 discharging concentrated runoff onto fills, erodible soils, unstable  
20 areas, and **connected headwall swales.**

21 (b) The following stabilization standards shall apply to logging road  
22 watercourse crossings:

23 (1) Bare soil on fills or sidecast associated with logging road  
24 watercourse crossings that are created or exposed by timber operations  
25 shall be stabilized to the extent necessary to minimize soil erosion  
and sediment transport and to prevent the discharge of sediment into

Formatted: Highlight

1 watercourses and lakes in ~~quantities deleterious~~ to the beneficial  
2 uses of water. Erosion control measures for the traveled surface of  
3 roads and landing surfaces are specified in 14 CCR §§ 923.5 [943.5,  
4 963.5] and 923.7 [943.7, 963.7]. Sites to be stabilized include, but  
5 are not limited to, sidecast or fill greater than 20 feet in slope  
6 distance from the outside edge of the road surface at the logging road  
7 watercourse crossing.

Formatted: Highlight

8 (2) Soil stabilization measures shall be described in the plan  
9 and ~~may~~ include, but are not limited to, removal, armoring with rip-  
10 rap, replanting, mulching, seeding, installing commercial erosion  
11 control devices to manufacturer's specifications, or chemical  
12 stabilizers.

Formatted: Highlight

13 (3) Soil stabilization treatments shall be in place upon  
14 completion of operations for the year of use or prior to October 15,  
15 whichever comes first. An exception is that bare areas created after  
16 October 15 shall be treated within 10 days or as agreed to by the  
17 Director.

18 (4) In watersheds with threatened or impaired values, within  
19 the WLPZ and within any ELZ or EEZ designated for watercourse or lake  
20 protection, treatments to stabilize soils, minimize soil erosion, and  
21 prevent the discharge of sediment into watercourses and lakes in  
22 ~~quantities deleterious~~ to aquatic species or the quality and  
23 beneficial uses of water, or that threaten to violate applicable water  
24 quality requirements, shall be described in the plan as follows:

25 (A) In addition to the requirements of subsections (b) (1)-  
(3), soil stabilization is required for ~~areas~~ the following: ~~greater~~

1 ~~than 100 continuous square feet where timber operations have exposed~~  
2 ~~bare soil.~~

3 ~~(B) Where straw mulch is used, the minimum straw coverage~~  
4 ~~shall be 90 percent, and any treated area that has not been subject to~~  
5 ~~reuse or has less than 90 percent surface cover shall be treated again~~  
6 ~~by the end of timber operations.~~

7 ~~(C) Where slash mulch is used, the minimum slash coverage~~  
8 ~~shall be 90 percent, or 75 percent where the slash is packed into the~~  
9 ~~ground surface through the use of a tractor or equivalent piece of~~  
10 ~~heavy equipment.~~

11 ~~(D) For areas disturbed from May 1 to October 15,~~  
12 ~~treatments shall be completed prior to the start of any rain that~~  
13 ~~causes overland flow across or along the disturbed surface that~~ ~~soils~~  
14 ~~deliver sediment into a watercourse or lake in~~ ~~quantities deleterious~~  
15 ~~to the beneficial uses of water.~~

16 ~~(E) For areas disturbed from October 15 to May 1,~~  
17 ~~treatment shall be completed prior to any day for which a chance of~~  
18 ~~rain of 30 percent or greater is forecast by the National Weather~~  
19 ~~Service or within 10 days, whichever is earlier.~~

20 ~~(i) Areas exceeding 100 continuous square feet where~~  
21 ~~timber operations have exposed bare~~ ~~soil.~~

22 ~~(ii) Disturbed road cut banks and~~ ~~fills,~~ ~~and~~

23 ~~(iii) Any other area of disturbed soil that threatens~~  
24 ~~to discharge sediment into water in quantities deleterious to the~~  
25 ~~quality and beneficial uses of water.~~

Formatted: Highlight

Formatted: Highlight

Comment [p89]: ASP subsection 916.9(n)(1)(B) has been deleted as it addresses tractor roads.

Comment [p90]: NOTE: 916.9(n)(2) has been deleted as it is addressed in statewide subsection 923.5(1) above.

1 (B) Where straw mulch is used, the minimum straw coverage  
2 shall be 90 percent, and any treated area that has been reused or has  
3 less than 90 percent surface cover shall be treated again by the end  
4 of timber operations.

5 (C) Where slash mulch is packed into the ground surface  
6 through the use of a tractor or equivalent piece of heavy equipment  
7 the minimum slash coverage shall be 75 percent.

8 (D) For areas disturbed from May 1 to October 15,  
9 treatment shall be completed prior to the start of any rain that  
10 causes overland flow across or along the disturbed surface that ~~could~~  
11 deliver sediment into a watercourse or lake in ~~quantities deleterious~~  
12 to the beneficial uses of water.

13 (E) For areas disturbed from October 15 to May 1,  
14 treatment shall be completed prior to any day for which a chance of  
15 rain of 30 percent or greater is forecast by the National Weather  
16 Service or within 10 days of disturbance, whichever is earlier.

**Comment [p91]:** NOTE: ASP subsection 916.9(n)(7) is not included here for logging road watercourse crossings.

17  
18  
19 **923.15, 943.15, 963.15 Logging Road Watercourse Crossing Use**

20  
21 The following use standards shall apply to logging road watercourse  
22 crossings:

23 (a) Logging road watercourse crossings shall be used in a manner that  
24 is consistent with the design, construction, and maintenance of the  
25 logging road along which they have been constructed (Refer to 14 CCR

1 §§ 923.2 [943.2, 963.2], 923.4 [943.4, 963.4], 923.6 [943.6, 963.6],  
2 and 923.7 [943.7, 963.7]).

3  
4 **923.16, 943.16, 963.16 Logging Road Watercourse Crossing Maintenance**  
5 **and Monitoring**

6  
7 The following maintenance and monitoring standards shall apply to  
8 logging road watercourse crossings:

9 **(a)** Logging road watercourse crossings shall be maintained as  
10 designed, constructed, and reconstructed during timber operations and  
11 throughout the prescribed maintenance period.

12 **(b)** Logging road watercourse crossings that are used in connection  
13 with stocking activities shall be maintained throughout such use, even  
14 if this extends beyond the prescribed maintenance period.

15 **(c)** Soil stabilization treatments on logging road watercourse  
16 crossing fills shall be maintained to minimize soil erosion and  
17 sediment transport and to prevent the discharge of sediment into  
18 watercourses and lakes in **quantities deleterious** to the beneficial  
19 uses of water.

20 **(d)** The plan shall identify measures to be used to reduce sediment  
21 delivery from logging road watercourse crossings where evidence of  
22 substantial soil erosion and discharge of sediment into watercourses  
23 and lakes in **quantities deleterious** to the beneficial uses of water is  
24 present at a logging road watercourse crossing used for timber  
25 operations. Where evidence of substantial soil erosion and discharge  
of sediment into watercourses and lakes in **quantities deleterious** to

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

1 the beneficial uses of water is present at a logging road watercourse  
2 crossing used for timber operations, additional measures shall be  
3 stated in the plan and installed, as needed, to minimize soil erosion  
4 and sediment transport and to prevent the discharge of sediment into  
5 watercourses and lakes in **quantities deleterious** to the beneficial  
6 uses of water.

Formatted: Highlight

7 (e) Logging road watercourse crossings used for timber operations  
8 shall be monitored, as needed, to comply with 14 CCR § 1050.

9 (f) Drainage structures and associated necessary protective  
10 structures shall be maintained, repaired, and replaced as needed to  
11 minimize crossing blockage and to provide for adequate capacity.

12 (g) In watersheds with threatened or impaired values, the erosion  
13 control maintenance period on logging road watercourse crossings that  
14 are not abandoned or deactivated in accordance with 14 CCR § 923.8  
15 [943.8, 963.8] shall be three years.

16  
17 **923.17, 943.17, 963.17 Logging Road Watercourse Crossing Removal**

18  
19 All logging road watercourse crossings that are proposed by the plan  
20 submitter to be removed, including temporary crossings and those along  
21 abandoned or deactivated logging roads, shall be removed as described  
22 in the plan and shall apply the following standards:

23 (a) Fills shall be excavated to form a channel that is as close as  
24 feasible to the natural watercourse grade and orientation and that is  
25 wider than the average natural channel, as observed upstream and  
downstream of the logging road watercourse crossing to be removed.

1 (b) The excavated material and any resulting cut bank shall be no  
2 greater than 65 percent (1.5:1, horizontal to vertical) from the  
3 outside edge of the constructed channel to prevent slumping, to  
4 minimize soil erosion and sediment transport, and to prevent the  
5 discharge of sediment into watercourses and lakes in **quantities**  
6 **deleterious** to the beneficial uses of water.

Formatted: Highlight

7 (c) Exposed soil associated with logging road watercourse crossing  
8 fill removal, including cut banks and excavated material, shall be  
9 stabilized during and upon completion of removal operations, as  
10 needed, or as otherwise specified in the rules by seeding, mulching,  
11 rock armoring, or other suitable treatment to minimize soil erosion  
12 and sediment transport and to prevent the discharge of sediment into  
13 watercourses and lakes in **quantities deleterious** to the beneficial  
14 uses of water.

Formatted: Highlight

15 (d) Appropriate drainage facilities shall be installed along removed  
16 logging road watercourse crossing approaches at locations that  
17 minimize the concentration of surface runoff and soil erosion and to  
18 prevent the discharge of sediment into watercourses and lakes in  
19 **quantities deleterious** to the beneficial uses of water.

Formatted: Highlight

20 (e) Where it is not feasible to remove a logging road watercourse  
21 crossing or its associated fill to the above standards, the plan shall  
22 identify how soil erosion and sediment transport **will** be minimized and  
23 how the discharge of **deleterious** quantities of sediment into  
24 watercourses and lakes **will** be prevented.

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

25 (f) Where a significant volume of sediment is stored upstream from a  
logging road watercourse crossing that is proposed to be removed, the

1 stored sediment shall be removed or stabilized, to the extent  
2 feasible, as described in the plan and in conformance with required  
3 DF&G 1600 agreements.

4 (g) All logging road watercourse crossings proposed for removal shall  
5 be removed upon completion of use by the first day of the winter  
6 period or as specified in the applicable DFG 1600 agreement, whichever  
7 is earlier, or as otherwise specified in the plan.

8 (h) Where the removal of an individual logging road watercourse  
9 crossing eliminates access to other temporary crossings, all such  
10 crossings shall be removed concurrently.

11 (i) If operations are conducted during the winter period, temporary  
12 logging road watercourse crossings shall be removed before the flow of  
13 water exceeds the capacity of the individual crossing.

14  
15 **Amend 1034. Contents of Plan**

16 (x) The information in subsections (1)-(4)(A), (5)(A)-(5)(K), if  
17 applicable, (6)(A)-(B), and (7)-(16) shall be clearly shown on a map  
18 that is based upon a U. S. Geological Survey topographic quadrangle  
19 map, or equivalent, published at a scale of 1:24,000 or larger—On  
20 titled USGS (if available) or equivalent topographic maps of a scale  
21 not less than 2" to the mile, the information in subsections (1-4),  
22 (8), (9), and (11-13) shall be clearly shown. The information in  
23 subsections (4)(B), (5)(A)-(5)(K), if applicable, and (6)(C) shall be  
24 clearly shown on a topographic map at a scale of 1/2 inch equals 1  
25 mile (1:126,720) or larger. Additional maps, which may be topographic  
or planimetric, may be used to provide the information required in the

1 other subsections, ~~to~~ ~~or~~ show specific details, and to improve map  
2 clarity. ~~The appurtenant roads referenced in subsection (4) may be~~  
3 ~~shown on a map which may be planimetric with a scale as small as one-~~  
4 ~~half inch equals one mile.~~ Color coding shall not be used. A legend  
5 shall be included indicating the meaning of the symbols used to depict  
6 operational features on maps. See the district rules for the  
7 appropriate minimum mapping acreages.

8 **(1)-(3) [No change]**

9 **(4)** ~~Location of public roads and those private roads to be used~~  
10 ~~for timber operations within the plan area, and private roads~~  
11 ~~appurtenant to the timber operations where such roads are under the~~  
12 ~~ownership or control of the timber owner, timberland owner, timber~~  
13 ~~operator, or submitter of the plan, and classification of all proposed~~  
14 ~~and existing logging roads as permanent, seasonal, or temporary roads.~~

15 The following logging road- and landing-related features shall be  
16 shown on a map of the appropriate type and scale as described in  
17 subsection (x) above:

18 (A) Location of logging roads within the harvest area,  
19 including those located in watercourses, lakes, WLPZs, marshes, wet  
20 meadows, or other wet areas and those proposed for abandonment or  
21 deactivation.

22 (B) Location of logging roads under the ownership or  
23 control of the timber owner, timberland owner, timber operator, or  
24 plan submitter that will be used for log hauling and that are between  
25 the harvest area and the first public road to be used for log hauling.

This shall include:

1 (i) Logging roads and landings located in  
2 watercourses, lakes, WLPZs, marshes, wet meadows, or other wet areas,  
3 other than at logging road watercourse crossings.

4 (ii) Logging roads and landings proposed for  
5 abandonment or deactivation.

6 (iii) Logging roads that provide access to rock pits  
7 and water drafting sites.

8 ~~(5) Probable location of proposed and existing landings in the~~  
9 ~~watercourse and lake protection zone, and landings outside the zone~~  
10 ~~that are greater than 1/4 acre in size or whose construction involves~~  
11 ~~substantial excavation. The following shall be mapped at the~~  
12 ~~appropriate scale required under subsection (x), whichever is~~  
13 ~~applicable, for all constructed and reconstructed logging roads and~~  
14 ~~landings, unless otherwise described:~~

15 ~~(A) Location of logging road grades greater than 15~~  
16 ~~percent for over 200 continuous feet or logging road grades exceeding~~  
17 ~~20 percent.~~

18 ~~(B) Location of road failures on existing logging roads to~~  
19 ~~be reconstructed.~~

20 ~~(C) Location of logging roads across and landings on~~  
21 ~~unstable areas or **connected headwall swales.**~~

22 ~~(D) Location of logging roads or landings within Class I,~~  
23 ~~II, III, or IV watercourses or lakes, WLPZs, marshes, wet meadows, or~~  
24 ~~other wet areas other than at logging road watercourse crossings.~~

1 (E) Location of logging roads and landings with  
2 insloping, inside ditch drainage, or crowning in excess of 300 lineal  
3 feet that drains into a classified watercourse or lake.

4 (F) Location of landings that require substantial  
5 excavation and landings in excess of one-quarter acre in size.

6 (G) Location of disposal sites for spoils generated during  
7 logging road or landing construction or reconstruction on slopes  
8 greater than 40 percent or on active unstable areas.

9 (H) Location of logging roads and landings across slopes  
10 greater than 65 percent for 100 lineal feet or more.

11 (I) Location of logging roads and landings across slopes  
12 greater than 50 percent for 100 lineal feet or more within 100 feet of  
13 the boundary of a WLPZ that drains toward the zoned watercourse or  
14 lake.

15 (J) In watersheds with threatened or impaired values, the  
16 location of active erosion sites on logging roads and landings that  
17 will be treated.

18 (K) Location of any other area(s) where non-standard  
19 practices on logging roads are proposed.

20 (6) The following logging road watercourse crossing-related  
21 features shall be shown on a map of the appropriate type and scale as  
22 described in subsection (x) above:

23 (A) Location of existing logging road watercourse  
24 crossings within the harvest area, including those crossings to be  
25 abandoned or deactivated. This requirement may be met by depicting  
the intersection of a logging road and a watercourse.

1 (B) Location of constructed and reconstructed logging road  
2 watercourse crossings within the harvest area, including those  
3 crossings to be abandoned or deactivated.

4 (C) The following logging road watercourse crossings,  
5 which are: (i) not within the harvest area but are under the  
6 ownership or control of the owner of the timberland where timber is  
7 proposed for harvest and (ii) between the harvest area and the first  
8 public road to be used for log hauling:

9 (i) Existing logging road watercourse crossings of  
10 Class I and Class II waters that will be used for log hauling.

11 (ii) Constructed and reconstructed logging road  
12 watercourse crossings that will be used for log hauling.

13 (iii) Existing logging road watercourse crossings to be  
14 abandoned or deactivated.

15 Existing logging road watercourse crossings may be shown by  
16 depicting the intersection of a logging road and a watercourse.

17 ~~(6) Road failures on existing roads to be reconstructed.~~

18 (7) Location of all tractor road watercourse crossings of  
19 classified watercourses except temporary crossings of Class III  
20 watercourses that are dry at the time of use ~~without flowing water~~  
21 during timber operations at that crossing.

22 (8) Location of erosion hazard rating areas, if more than one  
23 rating exists.

24 (9) Location of watercourses and lakes with Class I, II, III,  
25 or IV waters.

(10) Location of known unstable areas or slides.

1 (11) Location of understocked areas prior to timber operations,  
2 and other areas not normally bearing timber to at least a 20-acre  
3 minimum, or as specified in the district rules.

4 (12) Location of boundaries of timber-site classes needed for  
5 determination of stocking standards to be applied, down to at least a  
6 20-acre minimum or as specified in the district rules.

7 (13) Location of main ridge tops on the logging area suitable  
8 for fire suppression efforts that will require the felling of snags.

9 (14) Location of Coastal Commission Special Treatment Areas or  
10 any special treatment area.

11 (15) Location for which heavy equipment use is proposed on  
12 unstable areas, or on areas for which tractor use is proposed beyond  
13 the limitations of the standard forest practice rules.

14 (16) Location of any in lieu use of heavy equipment and location  
15 of tractor roads other than crossings in the watercourses, lakes  
16 WLPZs, marshes, wet meadows, and other wet areas.

17 ~~(17) Location of any new or reconstructed road segment(s) that~~  
18 ~~exceed an average 15% grade for over 200 feet.~~

19 **(aa) - (bb) [No change]**

20 **(cc)** Explanation and justification for use of watercourses, marshes,  
21 wet meadows, and other wet areas as ~~landings, roads, or skid trails~~  
22 tractor roads.

23 **(dd) - (ee) [No change]**

24 **(ff)** ~~Explanation and justification for landings that exceed the~~  
25 ~~maximum size specified in the rules.~~

1 ~~(gg)~~ Any other information required by the rules or the Act to be  
2 included in the plan. The district rules provide for exceptions and  
3 alternatives to standard requirements that require inclusion of  
4 information in the THP.

5 ~~(hh)~~ Where roads, watercourse crossings, and associated landings in  
6 the logging area will be abandoned, the methods for abandonment shall  
7 be described.

8 ~~(ii)~~ On a map complying with subsection 1034(x), the locations and  
9 classifications of roads, watercourse crossings, and landings to be  
10 abandoned shall be shown.

11 ~~(jj)~~ (gg) A general description of physical conditions at the plan  
12 site, including general soils and topography information, vegetation  
13 and stand conditions, and watershed and stream conditions.

14 (hh) Option 1: All logging roads and all landings requiring  
15 construction or reconstruction along non-public roads that are not  
16 within the harvest area nor under the ownership or control of the  
17 timberland owner whose land is being harvested shall be identified.

18 Option 2: [Do not adopt the contents of subsection (hh) proposed  
19 under Option 1 and begin re-numbering subsection (ii) as (hh), (jj) as  
20 (ii), etc.]

21 (ii) The following shall be disclosed and described in the plan for  
22 all constructed and reconstructed logging roads and landings:

23 (1) Option 1: Lineal distance of individual segments of  
24 logging road construction.

25 Option 2: Total lineal distance of all logging road  
construction.

1 (2) Potential public safety concerns.

2 (3) Logging roads wider than single lane compatible with the  
3 largest type of equipment specified for use.

4 (4) Areas with identified isolated outcrops of asbestos-bearing  
5 soil or parent material.

6 (5) Areas with potential mercury in soil, fills, or mine  
7 tailings.

8 (6) Areas where rules require a constructed bench to support  
9 fill on slopes greater than 50 percent for 100 lineal feet or more.

10 (7) Landings in excess of one-quarter acre on slopes exceeding  
11 40 percent.

12 (8) Logging roads across or landings on unstable areas or  
13 connected headwall swales.

14 (9) Logging roads or landings within Class I, II, III, or IV  
15 watercourses or lakes, WLPZs, marshes, wet meadows, or other wet areas  
16 other than at logging road watercourse crossings.

17 (10) Logging road and landing insloping, inside ditch drainage,  
18 or crowning in excess of 300 lineal feet that drains to a classified  
19 watercourse or lake.

20 (11) Road failures on existing logging roads to be  
21 reconstructed.

22 (12) Disposal sites for spoils generated during logging road or  
23 landing construction or reconstruction on slopes greater than 40  
24 percent or on active unstable areas.

1 (13) Logging roads and landings across slopes greater than 50  
2 percent for 100 lineal feet or more within 100 feet of the boundary of  
3 a WLPZ that drains toward the zoned watercourse or lake.

4 (14) Logging roads and landings across or landings on slopes  
5 greater than 65 percent for 100 lineal feet or more.

6 (15) Logging roads or landings to be abandoned or deactivated,  
7 including specific measures used to apply the general abandonment or  
8 deactivation requirements of 14 CCR § 923.8 [943.8, 963.8].

9 (16) Landings that require substantial excavation and landings  
10 in excess of one-quarter acre in size.

11 (17) Any other areas where non-standard practices on logging  
12 roads or landings are proposed.

13 (jj) In watersheds with ~~listed anadromous salmoids~~~~threatened or~~  
14 ~~impaired values~~, the following shall be disclosed in the plan:

15 (1) ~~Active erosion~~-Erosion sites on logging roads and landings,  
16 that will be ~~treated~~.

17 (2) ~~Identification and description of specific provisions for~~  
18 ~~a~~All proposed logging road construction on slopes greater than 50  
19 ~~percent~~.

20 (3) ~~OPTION 1: Disclose and describe all existing permanent~~  
21 ~~logging road watercourse~~ ~~crossings~~.

22 (11) The following shall be provided in the plan for all constructed  
23 and reconstructed logging road watercourse crossings:

24 (1) Describe all constructed or reconstructed logging road  
25 watercourse crossings within the harvest area, as needed.

**Comment [p92]:** Re-worded rule language required per 923.2(f).

**Comment [p93]:** Required per 923.4(s).

**Comment [p94]:** Option 1 approach to address 923.11(k)(1) related to existing crossings.

1 OPTION 2: (A) Disclose and describe all existing permanent  
2 logging road watercourse crossings.

3 (2) Option 1: Disclose and describe all permanent and temporary  
4 logging road watercourse crossings requiring construction or  
5 reconstruction along non-public roads, except temporary logging road  
6 watercourse crossings of Class III watercourses that are dry at the  
7 time of use, that are not within the harvest area nor under the  
8 ownership or control of the timberland owner where timber is proposed  
9 for harvest. Option 2: [Do not adopt the contents of subsection  
10 (11) (3) proposed under Option 1 and begin re-numbering subsection  
11 (11) (3) as (11) (2), (11) (4) as (11) (3), etc.]

12 (3) Disclose the potential public safety impacts where crossing  
13 construction or reconstruction may affect public safety. (Refer to 14  
14 CCR § 923.10(e) [943.10(e), 963.10(e)].

15 (4) Disclose how diversions at logging road watercourse  
16 crossings will be avoided. (Refer to 14 CCR § 923.10(g) [943.10(g),  
17 963.10(g)].

18 (5) Include the analyses and specifications that demonstrate  
19 all permanent constructed and reconstructed logging road watercourse  
20 crossing structures installed within Class I watercourses, classified  
21 based upon biological characteristics, will be designed to allow for  
22 upstream and downstream passage of fish or listed aquatic species  
23 during any life stage and for the natural movement of bedload. (Refer  
24 to 14 CCR § 923.11(i) [943.11(i), 963.11(i)].

25 (6) Specify the minimum diameter of the culvert and the method  
used to determine the culvert diameter where new culverts are proposed

**Comment [p95]:** Option 2 addresses 923.11(k)(1) related to existing crossings under a subsection heading that refers to constructed and reconstructed crossings. Note: This option does not appear to be logical. It would also make this a statewide requirement instead of only in watersheds with listed anadromous salmonids.

**Comment [p96]:** Requires disclosure and description of all constructed and reconstructed logging road watercourse crossing that are either permanent or temporary (except dry CIII crossings).

1 for permanent installation at a logging road watercourse crossing.

2 (Refer to 14 CCR § 923.11(e) [943.11(e), 963.11(e)].)

3 (7) State the range of required rock dimensions for rock used  
4 in logging road watercourse crossings utilizing fords. (Refer to 14  
5 CCR § 923.11(h) [943.11(h), 963.11(h)].)

6 (8) Identify protection measures needed to reduce sediment  
7 delivery where evidence of substantial soil erosion and discharge of  
8 sediment into watercourses or lakes in **quantities deleterious** to the  
9 beneficial uses of water is present at a logging road watercourse  
10 crossing used for timber operations. (Refer to 14 CCR § 923.16(d)  
11 [943.16(d), 963.16(d)].)

Formatted: Highlight

12 (9) Identify how soil erosion and sediment transport will be  
13 minimized and how the discharge of **deleterious** quantities of soil into  
14 watercourses or lakes will be prevented where it is not feasible to  
15 remove a logging road watercourse crossing or its associated fill to  
16 the standards contained in 14 CCR § 923.17 [943.17, 963.17]. (Refer  
17 to 14 CCR § 923.17(e) [943.17(e), 963.17(e)].)

Formatted: Highlight

18 (10) Disclose and describe site conditions, and, to the extent  
19 feasible, specify measures to be taken to address potential sediment  
20 mobilization where a significant volume of sediment is stored upstream  
21 from a logging road watercourse crossing that is proposed to be  
22 removed. (Refer to 14 CCR § 923.17(f) [943.17(f), 963.17(f)].)

23 (11) In watersheds with threatened or impaired values, the  
24 following shall apply:

25 (A) State how existing permanent culverts used for logging  
road watercourse crossings on Class I watercourses, classified based

1 upon biological characteristics, shall be brought up to the standards  
2 of 14 CCR § 923.11(c) [943.11(c), 963.11(c)]. (Refer to 14 CCR §  
3 923.11(i) [943.11(i), 963.11(i)].)

4 **(B) Option 1:** Where logging road networks are remote or  
5 are located where the landscape is unstable, where crossing fills over  
6 culverts are large, or where logging road watercourse crossing  
7 drainage structures and erosion control features historically have a  
8 high failure rate and where drainage structures and erosion control  
9 features will be oversized, designed for low maintenance, or  
10 reinforced, the method of analysis and the design for crossing  
11 protection shall be included in the plan. (Refer to 14 CCR §  
12 923.10(j)(2) [943.10(j)(2), 963.10(j)(2)].)

13 **Option 2 [This only applies if 14 CCR § 923.10(h)**  
14 **[943.10(h), 963.10(h)], Option 1 is adopted]:** In addition to the  
15 requirements of 923.11(h), include the method of analysis and the  
16 design for logging road watercourse crossing protection. (Refer to 14  
17 CCR § 923.10(j)(2) [943.10(j)(2), 963.10(j)(2)].)

18 **Option 3: [This only applies if 14 CCR § 923.10(h)**  
19 **[943.10(h), 963.10(h)], Option 1 is adopted: Do not adopt Option 1 or**

20 **Option 2.]**

21  
22 **Amend 1051.1. Contents of Modified THP**

23  
24 A plan submitted under ~~section~~ 14 CCR § 1051 above shall contain all  
25 the provisions of 14 CCR § 1034 except the following: (o), (x)(6),  
(x)(7), (z), (cc), (dd), (ee), (ff), and (ll), and the RPF shall:

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

**Amend 1090.5 Contents of NTMP**

(w) On a USGS quadrangle or equivalent topographical map of a scale not less than 2" to the mile, the following information shall be clearly provided. Additional maps may be required to show specific details, and may be planimetric. Color coding shall not be used. A legend shall be included indicating the meaning of the symbols used to depict operational features on maps. See the district rules for the appropriate minimum mapping acreages.

(1)-(3) [No change]

(4) Location of public roads within the ~~plan~~ harvest area, and private roads appurtenant to the timber operations where such roads are under the ownership or control of the timberland owner and are contiguous with the ~~plan~~ harvest area, and classification of all proposed and existing logging roads as permanent, seasonal, or temporary roads.

(5)-14) [No change]

(x)-(ff) [No change]

(gg) Where logging roads, logging road watercourse crossings, and associated landings in the logging area will be abandoned or deactivated, the methods for abandonment or deactivation shall be described.

(hh) On a map complying with ~~subsection~~ 14 CCR § 1090.6(x) 1090.5(w), the locations and classifications of logging roads, logging road

1 watercourse crossings, and landings to be abandoned or deactivated  
2 shall be shown.

3 (ii) [No change]

4  
5 **Amend 1090.7 Notice of Timber Operations Content**

6  
7 (n) On a USGS quadrangle or equivalent map of a scale not less than  
8 2" to the mile, the following information pertinent to the Notice of  
9 Operations shall be clearly provided. Additional maps may be required  
10 to show specific details, and may be planimetric. Color coding shall  
11 not be used. A legend shall be included indicating the meaning of the  
12 symbols used to depict operational features on maps. See the district  
13 rules for the appropriate minimum mapping acreages.

14 (1)-(3) [No change]

15 (4) Location of public roads within the Notice area, and  
16 private roads appurtenant to the timber operations where such roads  
17 are under the ownership or control of the timberland owner, and are  
18 contiguous with the Notice area, and classification of all proposed  
19 and existing logging roads as permanent, seasonal, or temporary roads.

20 (5)-(11) [No change]

21  
22 **Amend 1092.09 PTHP Contents**

23  
24 (1) On a ~~titled USGS quadrangle or equivalent topographic map of a~~  
25 ~~scale not less than 2" to the mile~~ map that is based upon a U. S.  
Geological Survey topographic quadrangle map, or equivalent, published

1 at a scale of 1:24,000 or larger, the information in subsections (1-5)  
2 (1)-(5)(A), (6)(A)-(6)(K), if applicable, (7)(A)-(B), and (7-11) shall  
3 be clearly shown. On a topographic map at a scale of 1/2 inch equals  
4 1 mile (1:126,720) or larger, the information in subsections (5)(B),  
5 (6)(A)-(6)(K), if applicable, and (7)(C) shall be clearly shown.

6 Additional maps, which may be topographic or planimetric, may be used  
7 to provide the information required in other subsections or show  
8 specific details, and to improve map clarity. The appurtenant roads  
9 referenced in subsection (5) may be shown on a map which may be  
10 planimetric with a scale as small as one half inch equals one mile.  
11 Color coding shall not be used. A legend shall be included indicating  
12 the meaning of the symbols used to depict operational features on  
13 maps. See the district rules for the appropriate minimum mapping  
14 acreage.

15 **(1)-(4) [No change]**

16 **(5)** ~~Location of public roads within the PTHP, and private roads~~  
17 ~~appurtenant to the timber operations where such roads are under the~~  
18 ~~ownership or control of the timber owner, timberland owner or timber~~  
19 ~~operator, and classification of all proposed and existing logging~~  
20 ~~roads as permanent, seasonal, or temporary roads. The following~~  
21 logging road- and landing-related features shall be shown on a map of  
22 the appropriate type and scale as described in subsection (1) above:

23 **(A)** Location of all logging roads within the harvest area,  
24 including those located in watercourses, lakes, WLPZs, marshes, wet  
25 meadows, or other wet areas and those proposed for abandonment or  
deactivation.

1           (B) Location of all logging roads that will be used for  
2 log hauling under the ownership or control of the timber owner,  
3 timberland owner, timber operator, or plan submitter that are between  
4 the harvest area and the first public road to be used for log hauling.

5 This shall include:

6           (i) Logging roads and landings located in  
7 watercourses, lakes, WLPZs, marshes, wet meadows, or other wet areas,  
8 other than at logging road watercourse crossings.

9           (ii) Logging roads and landings proposed for  
10 abandonment or deactivation.

11           (iii) Logging roads that provide access to rock pits  
12 and water drafting sites.

13           (6) The following shall be mapped at the appropriate scale  
14 required under subsection (1), whichever is applicable, for all  
15 constructed and reconstructed logging roads and landings, unless  
16 otherwise noted:

17           (A) Location of logging road grades greater than 15  
18 percent for over 200 continuous feet or logging road grades greater  
19 than 20 percent.

20           (B) Location of road failures on existing roads to be  
21 reconstructed.

22           (C) Location of logging roads across or landings on  
23 unstable areas or **connected headwall swales.**

24           (D) Location of logging roads or landings within Class I,  
25 II, III, or IV watercourses or lakes, WLPZs, marshes, wet meadows, or  
other wet areas other than at logging road watercourse crossings.

1 (E) Location of logging road and landing insloping, inside  
2 ditch drainage, or crowning in excess of 300 lineal feet that drains  
3 to a classified watercourse or lake.

4 (F) Location of landings that require substantial  
5 excavation and landings in excess of one-quarter acre in size.

6 (G) Location of disposal sites for spoils generated during  
7 logging road or landing construction or reconstruction on slopes  
8 greater than 40 percent or on active unstable areas.

9 (H) Location of logging roads and landings across slopes  
10 greater than than 65 percent for 100 lineal feet or more.

11 (I) Location of logging roads and landings across slopes  
12 greater than 50 percent for 100 lineal feet or more within 100 feet of  
13 the boundary of a WLPZ that drains toward the zoned watercourse or  
14 lake.

15 (J) In watersheds with threatened or impaired values, the  
16 location of active erosion sites on logging roads and landings that  
17 will be treated.

18 (K) Location of any other area(s) where non-standard  
19 practices on logging roads are proposed.

20 ~~(7)-(6)~~ Location of proposed and existing landings in the  
21 watercourse and lake protection zone, and landings outside the zone  
22 that are greater than 1/4 acre in size or whose construction involves  
23 substantial excavation. The following logging road watercourse  
24 crossing-related items shall be shown on a map of the appropriate type  
25 and scale as described in subsection (1) above:

1 (A) Location of all existing logging road watercourse  
2 crossings within the harvest area, including those proposed for  
3 abandonment or deactivation. This requirement may be met by depicting  
4 the intersection of a logging road and a watercourse.

5 (B) Location of all constructed or reconstructed logging  
6 road watercourse crossings within the harvest area, including those  
7 proposed for abandonment or deactivation.

8 (C) The following logging road watercourse crossings,  
9 which are: (i) not within the harvest area but are under the  
10 ownership or control of the owner of the timberland where timber is  
11 proposed for harvest and (ii) between the harvest area and the first  
12 public road to be used for log hauling:

13 (i) Existing logging road watercourse crossings of  
14 Class I and Class II waters that will be used for log hauling.

15 (ii) Constructed and reconstructed logging road  
16 watercourse crossings that will be used for log hauling.

17 (iii) Existing logging road watercourse crossings to be  
18 abandoned or deactivated.

19 Existing logging road watercourse crossings may be shown by  
20 depicting the intersection of a logging road and a watercourse.

21 ~~(8) (7) Road failures on existing roads to be reconstructed.~~

22 ~~(8) Location of all tractor road watercourse crossings of~~  
23 ~~classified watercourses except temporary crossings of class III~~  
24 ~~watercourses that are dry at the time of use without flowing water~~  
25 ~~during timber operations at that crossing.~~

1 (9) Location of erosion hazard rating areas, if more than one  
2 rating exists.

3 (10) Location of watercourses and lakes with Class I, II, III or  
4 IV waters.

5 (11) Location of known unstable areas or slides.

6 (12) Location of unique areas.

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25